INDUSTRIAL COMPONENT DATA

EMD-BL-PH-480-PT 2903528 PHOENIX CONTACT Monitoring relay

Brand: PHOENIX CONTACT | Manufacturer Part Number: EMD-BL-PH-480-PT



Manufacturer	PHOENIX CONTACT
MPN / Reference	EMD-BL-PH-480-PT
Catalog number	2903528
Category	Phase monitoring relay
Minimum order	1 Pcs
Document ID	EO-D9CBBDA58B
Generated	2026-11-19

Product Overview

Monitoring relay
Control relay for phase sequence monitoring and asymmetry in three-phase voltages with 208 ... 480 V AC/120...277 V AC, configurable asymmetry, 1 switched contact, with push-in connection
Monitoring relay for monitoring the phase sequence and asymmetry of 3-phase voltages at 208 ... 480 V AC / 120 ... 277 V AC, configurable asymmetry, 1 changeover contact, with Push-in connection

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Relays

Additional Product Information

Key Commercial Data
Orderkey 2903528
Packing unit 1 pc
Catalog page Page 263 (C-5-2017)
GTIN 4046356747240
Weight per Piece (excluding packing) 71.200 g
Custom tariff number 85364900
Country of origin AT (Austria)
Dimensions
Width 17.5 mm
Height 88 mm

Depth 65.5 mm
Ambient conditions
Ambient temperature (operation) -25 °C ... 55 °C
Ambient temperature (storage/transport) -25 °C ... 70 °C
Connection data
Connection method Push-in connection
Conductor cross section solid min. 0.14 mm²
Conductor cross section solid max. 2.5 mm²
Conductor cross section AWG min. 26
Conductor cross section AWG max. 14
Conductor cross section flexible min. 0.14 mm²
Conductor cross section flexible max. 2.5 mm²
Stripping length 8 mm
General
Status display Yellow LED
Overvoltage category III, 300 V basic insulation (DIN EN 60947-5-1)
Rated insulation voltage 519 V (Supply circuit/measuring circuit (DIN EN 60947-5-1))
Electromagnetic compatibility Conformance with EMC Directive 2014/30/EU
Noise emission EN 61000-6-3
Noise immunity EN 61000-6-2
Color gray
Mounting position any
Assembly instructions on standard DIN rail NS 35 in accordance with EN 60715
Conformance CE-compliant
UL, USA/Canada UL/C-UL listed UL 508
Standards and Regulations
Electromagnetic compatibility Conformance with EMC Directive 2014/30/EU
Noise emission EN 61000-6-3
Noise immunity EN 61000-6-2
Low Voltage Directive Conformance with Low Voltage Directive 2006/95/EC (valid until 2016-04-19) / 2014/35/EU (valid from 2016-04-20)
Confor...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / EMD-BL-PH-480-PT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.