INDUSTRIAL COMPONENT DATA

EMD-SL-3V-400-N 2885278 PHOENIX CONTACT Monitoring relay

Brand: PHOENIX CONTACT | Manufacturer Part Number: EMD-SL-3V-400-N



Manufacturer	PHOENIX CONTACT
MPN / Reference	EMD-SL-3V-400-N
Catalog number	2885278
Category	Voltage monitoring relay
Minimum order	1 Pcs
Document ID	EO-E3A16163E2
Generated	2026-11-18

Product Overview

Monitoring relay
Supervisory relay for 3-phase voltage monitoring of 280...520 V AC, Window, with neutral connection, selectable supply voltage via power module, 1 switched contact

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Relays

Additional Product Information

Key Commercial Data
Orderkey 2885278
Packing unit 1 pc
Catalog page Page 269 (C-5-2017)
GTIN 4017918996512
Weight per Piece (excluding packing) 133.300 g
Custom tariff number 85364900
Country of origin AT (Austria)
Dimensions
Width 22.5 mm
Height 90 mm
Depth 113 mm
Ambient conditions

Ambient temperature (operation) -25 °C ... 55 °C
-25 °C ... 40 °C (corresponds to UL 508)
Ambient temperature (storage/transport) -25 °C ... 70 °C
Input data
Nominal input voltage UN 3 N ~ 400/230 V
Maximum temperature coefficient < 0.1 %/K
Function Window, with neutral conductor connection
Min. setting range -30 % ... 20 % (From UN)
Max. setting range -20 % ... 30 % (From UN)
Min setting range of the voltage threshold value 280 V AC ... 480 V AC
Max. setting range of the voltage threshold value 320 V AC ... 520 V AC
Setting range for response delay 0.2 s ... 10 s
Basic accuracy ± 5 % (of scale end value)
Setting accuracy <= 5 % (of scale end value)
Repeat accuracy <= 2 %
Voltage influence <= 0.5 %
Recovery time 500 ms
Contact side
Contact type 1 floating PDT
Maximum switching voltage 250 V AC (in acc. with IEC 60664-1)
Interrupting rating (ohmic load) max. 750 VA (3 A/250 V AC, module aligned, <= 5 mm spacing)
1250 VA (5 A/250 V AC, module not aligned, >= 5 mm spacing)
Output fuse 5 A (fast-blow)
Power supply
Supply voltage range 24 V AC ... 230 V AC (see Power modules)
24 V DC (see Power modules)
General
Mechanical service life approx. 2x 107cycles
Operating mode 100% operating factor
Mounting posi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / EMD-SL-3V-400-N with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.