INDUSTRIAL COMPONENT DATA

UM-PRO 122 FOOT BK 2200160 PHOENIX CONTACT Foot element

Brand: PHOENIX CONTACT | Manufacturer Part Number: UM-PRO 122 FOOT BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	UM-PRO 122 FOOT BK
Catalog number	2200160
Category	Extruded profile modular housing
Minimum order	10 Pcs
Document ID	EO-3FF1B52E74
Generated	2026-11-18

Product Overview

Foot element
Extruded profile housings, Rail mounting, DIN rail floor element for mounting under UM-PRO PROFILE (width: 122 mm), colour: black (9005), floor element, width: 14.3 mm, height: 135.9 mm, depth: 20.95 mm
Press-drawn section housings, DIN rail mounting, Base element for the DIN rail, for mounting below UM-PRO PROFILE (width: 122 mm), Foot element, width: 14.3 mm, height: 135.9 mm, depth: 20.95 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)

Additional Product Information

Technical dataNotesAssembly note Refer to the data sheet for the range in the download area.
Product propertiesProduct type Base latches
Housing type Press-drawn section housings
Housing series UM-PRO
Product family UM-PRO
Type Base element for the DIN rail, for mounting below UM-PRO PROFILE (width: 122 mm)
Data management status
Article revision 00
DimensionsWidth 14.3 mm
Height 135.9 mm
Depth 20.95 mm

Material specificationsColor (Housing) black (RAL 9005)
Flammability rating according to UL 94 V0
Housing material Polyamide
Surface characteristics untreated
Environmental and real-life conditionsThermal stability / ball thrust test
Specification IEC 60695-10-2:2014-02
Temperature 125 °C
Test duration 1 h
Force 20 N
Mechanical strength / tumbling barrel
Specification IEC 60068-2-31:2008-05
Height of fall 50 cm
Frequency 50
Ambient conditions
Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)
Ambient temperature (storage/transport) -40 °C ... 55 °C
Ambient temperature (assembly) -5 °C ... 100 °C
Relative humidity (storage/transport) 80 %
MountingMounting type DIN rail mounting
Packaging specificationsType of packaging packed in cardboard
Outer packaging type Carton

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UM-PRO 122 FOOT BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.