INDUSTRIAL COMPONENT DATA

IB IL AO 4/I/4-20-ECO 2702497 PHOENIX CONTACT Inline terminal

Brand: PHOENIX CONTACT | Manufacturer Part Number: IB IL AO 4/I/4-20-ECO



Manufacturer	PHOENIX CONTACT
MPN / Reference	IB IL AO 4/I/4-20-ECO
Catalog number	2702497
Category	Fieldbus, decentr. periphery - analogue I/O module
Minimum order	1 Pcs
Document ID	EO-50082CF19D
Generated	2026-11-19

Product Overview

Inline terminal
Inline, Analog output terminal, Analog outputs: 4, 4 mA ... 20 mA, connection technology: 2 conductors, transmission speed on the local bus: 500 kBit/s, protection index: IP20, Inline connector included

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > I/O

Additional Product Information

Key Commercial Data
Orderkey 2702497
Packing unit 1 pc
Catalog page Page 142 (C-6-2017)
GTIN 4055626204499
Weight per Piece (excluding packing) 84.100 g
Custom tariff number 85389091
Country of origin DE (Germany)
Note
Utilization restriction 1
Dimensions
Dimensional drawing
Width 12.2 mm

Height 119.8 mm
Depth 71.5 mm
Ambient conditions
Ambient temperature (operation) 0 °C ... 55 °C (see “Derating” table in the data sheet)
Ambient temperature (storage/transport) -25 °C ... 85 °C
Permissible humidity (operation) 10 % ... 95 % (according to DIN EN 61131-2)
Permissible humidity (storage/transport) 10 % ... 95 % (according to DIN EN 61131-2)
Air pressure (operation) 70 kPa ... 106 kPa (up to 3000 m above sea level)
Air pressure (storage/transport) 70 kPa ... 106 kPa (up to 3000 m above sea level)
Degree of protection IP20
General
Mounting type DIN rail
Net weight 84.1 g
Note on weight specifications with connector
Diagnostics messages Failure of the internal I/O supply I/O error message sent to the bus coupler
Checksum error I/O error message sent to the bus coupler
Interfaces
Designation Inline local bus
No. of channels 2
Connection method Inline data jumper
Transmission speed 500 kbps
Inline potentials
Designation Communications power (UL)
Supply voltage 7.5 V DC (via voltage jumper)
Current consumption typ. 40 mA
max. 50 mA
Designation Supply of analog modules (UANA)
Supply voltage 24 V DC (via voltage jumper)
Supply voltage range 19.2 V DC ... 30 V DC (including all toleranc...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / IB IL AO 4/I/4-20-ECO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.