INDUSTRIAL COMPONENT DATA

MSTBO 2,5/ 3-G1L GY 2909549 PHOENIX CONTACT Feed-through header

Brand: PHOENIX CONTACT | Manufacturer Part Number: MSTBO 2,5/ 3-G1L GY



Manufacturer	PHOENIX CONTACT
MPN / Reference	MSTBO 2,5/ 3-G1L GY
Catalog number	2909549
Category	Printed circuit board connector
Minimum order	200 Pcs
Document ID	EO-B403F5C7AC
Generated	2026-11-19

Product Overview

Feed-through header
Printed circuit board base housing, nominal section: 2.5 mm², color: gray, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Sn, contact connection type: Male, number of potentials: 3, number of rows: 1, number of poles: 3, number of connections: 3, family of articles: MSTBO 2.5/.. -G1L, pitch: 5 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 3.5 mm, number of solder pins per potential: 1, plug-in system: COMBICON MSTB 2.5, lock: without, packaging type: boxed packed, Item with side pin output on the left

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)

Additional Product Information

Key Commercial Data
Orderkey 2909549
Packing unit 200 pc
GTIN 4017918404598
Weight per Piece (excluding packing) 1.770 g
Custom tariff number 85366990
Country of origin PL (Poland)
Dimensions
Pitch 5 mm
Dimension a 10 mm

Height 15 mm
General
Range of articles MSTBO 2,5/..-G1L
Insulating material group IIIa
Rated surge voltage (III/3) 4 kV
Rated surge voltage (III/2) 4 kV
Rated surge voltage (II/2) 4 kV
Rated voltage (III/3) 250 V
Rated voltage (III/2) 320 V
Rated voltage (II/2) 400 V
Connection in acc. with standard EN-VDE
Nominal current IN 12 A
Maximum load current 12 A
Insulating material PBT
Flammability rating according to UL 94 V0
Number of positions 3
Standards and Regulations
Connection in acc. with standard EN-VDE
CSA
Flammability rating according to UL 94 V0
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Classifications
eCl@ss 4.027180401eCl@ss 4.127180401eCl@ss 5.027180506eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss 7.027440402eCl@ss 8.027440402eCl@ss 9.027440402
ETIM 2.0EC001031ETIM 3.0EC001031ETIM 4.0EC002637ETIM 5.0EC002637ETIM 6.0EC002637
UNSPSC 6.0131261501UNSPSC 7.090131261501UNSPSC 1131261501UNSPSC 12.0131261501UNSPSC 13.239121409

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MSTBO 2,5/ 3-G1L GY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.