INDUSTRIAL COMPONENT DATA

MSTBO 2,5/ 4-G1R BUGY CD:2,4 1107236 PHOENIX CONTACT PCB headers, number of positions: 4, pitch: 5 mm, pin l..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MSTBO 2,5/ 4-G1R BUGY CD:2,4



Manufacturer	PHOENIX CONTACT
MPN / Reference	MSTBO 2,5/ 4-G1R BUGY CD:2,4
Catalog number	1107236
Category	Printed circuit board connector
Minimum order	500 Pcs
Document ID	EO-A7157F0F8B
Generated	2026-11-19

Product Overview

PCB headers, number of positions: 4, pitch: 5 mm, pin layout: Linear pinning
Printed circuit board base housing, nominal section: 2.5 mm², color: bluish gray, nominal current: 12 A, nominal voltage (III/2): 320 V, contact type: Male, number of rows: 1, number of poles: 4, family of articles: MSTBO 2.5/.. -G1R, pitch: 5 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 3.5 mm, number of solder pins per potential: 1, plug-in system: COMBICON MSTB 2.5, lock: without, packaging type: boxed, Item with right side pin output
PCB headers, nominal cross section: 2.5 mm2, color: blue grey, nominal current: 12 A, rated voltage (III/2): 320 V, contact surface: Sn, contact connection type: Pin, number of rows: 1, number of positions: 4, product range: MSTBO 2,5/..-G1R, pitch: 5 mm, connection method: pluggable, mounting: Wave soldering, pin layout: Linear pinning, solder pin [P]: 3.5 mm, number of solder pins per potential: 1, plug-in system: COMBICON MSTB 2,5, Pin connector pattern alignment: Orthogonal, locking: without, type of packaging: packed in cardboard, Fixed coding of the positions: 2, 4, item with lateral pin outlet on the right

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)

Additional Product Information

Technical dataProduct propertiesProduct type PCB headers
Product family MSTBO 2,5/..-G1R
Product line COMBICON Connectors M
Type Header perpendicular to the PCB
Number of positions 4

Pitch 5 mm
Number of rows 1
Pin layout Linear pinning
Solder pins per potential 1
Data management status
Article revision 03
Electrical propertiesNominal current IN 12 A
Nominal voltage UN 250 V
Contact resistance 1.6 m?
Rated voltage (III/3) 250 V
Rated surge voltage (III/3) 4 kV
Rated voltage (III/2) 320 V
Rated surge voltage (III/2) 4 kV
Rated voltage (II/2) 630 V
Rated surge voltage (II/2) 4 kV
MountingMounting type Wave soldering
Pin layout Linear pinning
Material specificationsMaterial data - contact
Note WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC JESD 201
Contact material Cu alloy
Surface characteristics tin-plated
Material data - housing
Color (Housing) blue grey (7031)
Insulating material PA
Insulating material group I
CTI according to IEC 60112 600
Flammability rating according to UL 94 V0
Glow wire flammability index GWFI according to EN 60695-2-12 850
Glow wire ignition temperature GWIT according to EN 60695-2-13 775
Temperature for the ball pressure test according to EN 60695-10-2 125 °C
DimensionsPitch 5 mm
Width [w] 19.95 mm
Height [h] 16.5 mm
Length [l] 14.65 mm
Solder pin length [P] 3.5 mm
Pin dimensions 1 x 1 mm
PCB design
Hole diameter 1.4 mm
Mechanical testsVisual inspection
Specification IEC 60512-1-1:2002-02
Result Test passed
Dimension check
Sp...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MSTBO 2,5/ 4-G1R BUGY CD:2,4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.