INDUSTRIAL COMPONENT DATA

SAC-5P- 2,0-PUR/FS SCO BK 1400570 PHOENIX CONTACT Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P- 2,0-PUR/FS SCO BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P- 2,0-PUR/FS SCO BK
Catalog number	1400570
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-374EDE33C8
Generated	2026-11-19

Product Overview

Sensor/actuator cable

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data
Orderkey 1400570
Packing unit 1
GTIN 4046356502818
Custom tariff number 85444290
Dimensions
Length of cable 2 m
Stripping length of the free conductor end 50 mm
Ambient conditions
Degree of protection IP65
IP67
IP68
General
Rated current at 40°C 4 A
Rated voltage 48 V AC

60 V DC
Number of positions 5
Insulation resistance >= 100 M?
Coding A - standard
Status display No
Overvoltage category II
Degree of pollution 3
Material
Flammability rating according to UL 94 HB
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material of grip body TPU, hardly inflammable, self-extinguishing
Material, knurls Zinc die-cast, nickel-plated
Sealing material NBR
Standards and Regulations
Flammability rating according to UL 94 HB
Cable
Cable type PUR halogen-free black
Cable type (abbreviation) PUR
UL AWM style 20549
Conductor cross section 5x 0.34 mm² (Signal line)
AWG signal line 22
Conductor structure signal line 42x 0.10 mm
Core diameter including insulation 1.27 mm ±0.02 mm (Signal line)
Thickness, insulation approx. 0.5 mm
Wire colors brown, white, blue, black, green-yellow
External sheath, color black-gray RAL 7021
External cable diameter D 4.55 mm ±0.15 mm
Smallest bending radius, fixed installation 23 mm
Smallest bending radius, movable installation 46 mm
Number of bending cycles 10000000
Bending radius 50 mm
Traversing path 10 m
Traversing rate 3 m/s
Acceleration 10 m/s²
Cable weight 33 kg/km
Outer sheath, material PUR
Material con...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P- 2,0-PUR/FS SCO BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.