INDUSTRIAL COMPONENT DATA

Q SET-PG9-0,75/3-ESA BK HUBA 1641824 PHOENIX CONTACT Connector set

Brand: PHOENIX CONTACT | Manufacturer Part Number: Q SET-PG9-0,75/3-ESA BK HUBA

PRODUCT IMAGE\nNOT AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	Q SET-PG9-0,75/3-ESA BK HUBA
Catalog number	1641824
Category	Sensor-actuator connector chassis
Minimum order	100 Pcs
Document ID	EO-56466523E1
Generated	2026-11-19

Product Overview

Connector set

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > QUICKON Installation System (QPD)

Additional Product Information

Key Commercial Data
Orderkey 1641824
Packing unit 100 pc
Minimum order quantity 100 pc
Note Made to Order (non-returnable)
GTIN 4017918890438
Weight per Piece (excluding packing) 6.000 g
Custom tariff number 39269097
Country of origin PL (Poland)
General
Connection If the conductor is reconnected, it must be cut off above the last contact point. QUICKON components may only be operated when under no load.
Color black
Connection method QUICKON connection
Number of positions 3

Wrench size, union nut 19 mm
Tightening torque, union nut 2.5 Nm
Wrench size, contact carrier 19 mm
Tightening torque contact carrier 3.75 Nm
Tightening torque, counter nut 3.75 Nm
Number of connections 3
Cabel
Wire insulation material PVC / PE
Wire diameter including insulation >= 2.5 mm
External cable diameter 6 mm ... 12 mm
Ambient conditions
Degree of protection IP65
IP67
Ambient temperature (operation) -25 °C ... 80 °C (Specifications of the cable manufacturer must be observed.)
-25 °C ... 50 °C (when the conductor is connected. Specifications of the cable manufacturer must also be observed.)
Temperature when conductor connected -5 °C ... 50 °C (specifications of the cable manufacturer must also be observed)
Mechanical characteristics
QUICKON connectability max. 10 (if the conductor is connected more than once, seal and cap may need to be replaced.)
Impact category 3
Category of shock impact IK07
Material data
Contact carrier material PA
Insulating material PA
Flammability rating according to UL 94 V...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / Q SET-PG9-0,75/3-ESA BK HUBA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.