INDUSTRIAL COMPONENT DATA

HCS-C MAXI 1W 2X9V 1 1 7035 2203170 PHOENIX CONTACT Electronic housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: HCS-C MAXI 1W 2X9V 1 1 7035



Manufacturer	PHOENIX CONTACT
MPN / Reference	HCS-C MAXI 1W 2X9V 1 1 7035
Catalog number	2203170
Category	Electronic enclosure
Minimum order	1 Pcs
Document ID	EO-B7AA3D9F9B
Generated	2026-11-19

Product Overview

Electronic housing
C-Maxi portable case in light gray, formed by two halves, two screens on the front side, screws. Front with 1.1 mm reinforcement, with window and keyboard slot, battery compartment cover and battery contacts 2 x 9 V blocks

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)

Additional Product Information

Key Commercial Data
Orderkey 2203170
Packing unit 1 pc
GTIN 4055626377261
Weight per Piece (excluding packing) 232.200 g
Custom tariff number 39269097
Country of origin DE (Germany)
Item properties
Type HCS-C MAXI 1W 2X9V 1 1 7035
Order No. 2203170
Housing type Handheld housing
Type straight
Battery compartment 2 x 9 V

Measurements
Dimensional drawing
Caption Schematic representation - for additional information, see product range drawing in the Download Center
Width [w] 94 mm
Height [h] 182.5 mm
Depth [d] 39 mm
Diagonal 2.8 in. (Window for display)
Dimensions 73 mm x 80 mm x 1.1 mm (Recessed area on front)
73 mm x 7.9 mm x 1.1 mm (Recessed area on front)
73 mm x 8 mm x 1.1 mm (Recessed area on front)
62 mm x 33 mm (Window for display)
Front with faceplate top, 1 x (73.8 mm x 25.8 mm)
bottom, 1 x (73.8 mm x 25.8 mm)
Material specifications
Color (RAL) light gray (7035)
Flammability rating according to UL 94 V0
Housing material ABS
Hammer test
Specification IEC 60068-2-75:2014-09
Impact energy 0.7 J
Number of drop cycles 5
Thermostability (ball thrust test)
Specification IEC 60695-10-2:2014-02
Temperature 80 °C
Test duration 1 h
Force 20
Test for assessing the risk of fire (glow wire)
Specification IEC 60695-2-11:2014-02
Temperature 850 °C
Time of exposure 30 s
Packaging information
Pieces per package 1
Denomination packing units Pcs.
Standards and regulations
Flammability rating according to UL 94 V0
Classifications
eCl@ss 5.127180506eCl@ss 6.027180800eCl@ss 7.02718270...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HCS-C MAXI 1W 2X9V 1 1 7035 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.