INDUSTRIAL COMPONENT DATA

FLKM 4X14-PA/SC/DIO/S7-1500 2907381 PHOENIX CONTACT Front adapters

Brand: PHOENIX CONTACT | Manufacturer Part Number: FLKM 4X14-PA/SC/DIO/S7-1500



Manufacturer	PHOENIX CONTACT
MPN / Reference	FLKM 4X14-PA/SC/DIO/S7-1500
Catalog number	2907381
Category	Accessories/spare parts for controls
Minimum order	1 Pcs
Document ID	EO-263D06862B
Generated	2026-11-19

Product Overview

Front adapters
VARIOFACE front adapter, with screw connection, for 35 mm digital modules of SIMATIC® S7-1500, 4x 8 or 2x 8 channel connection possible.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Key Commercial Data
Orderkey 2907381
Packing unit 1 pc
Catalog page Page 510 (C-5-2017)
GTIN 4055626256511
Weight per Piece (excluding packing) 108.770 g
Custom tariff number 85369010
Country of origin RO (Romania)
Ambient conditions
Ambient temperature (operation) -25 °C ... 60 °C
Ambient temperature (storage/transport) -40 °C ... 70 °C
General
Max. permissible operating voltage < 50 V DC

Max. permissible current 1 A (per path)
Max. permissible total current 3 A (per byte when supplying from the module side)
12 A (When supplying via the front adapter)
Nominal operating mode 100% operating factor
Degree of protection IP20
Connection data 1
Connection name Field level
Connection method IDC/FLK pin strip
Number of connections 4
Number of positions 14
Channels which can be connected 32
Pitch 2.54 mm
Connection data 2
Connection name Field level
Connection method IDC/FLK pin strip
Number of connections 2
Number of positions 14
Channels which can be connected 16
Pitch 2.54 mm
Connection data 3
Connection name Supply
Connection method Screw connection
Stripping length 10 mm
Conductor cross section solid 0.25 mm² ... 1.5 mm² (with ferrule)
0.5 mm² ... 2.5 mm² (without ferrule)
Conductor cross section flexible 0.25 mm² ... 1.5 mm² (with ferrule)
0.5 mm² ... 2.5 mm² (without ferrule)
Torque 0.4 Nm
Supported controller
Controller SIEMENS S7-1500
- suitable I/O card 6ES7 521-1BH00-0AB0
6ES7 521-1BH50-0AA0
6ES7 521-1BL00-0AB0
6ES7 522-1BH00-0AB0
6ES7 522-1BH01-0AB0
6ES7 522-1BL00-0AB0
6...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FLKM 4X14-PA/SC/DIO/S7-1500 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.