

## INDUSTRIAL COMPONENT DATA

# MKDSN 1,5/10-5,08 BD:86-25 1704731 PHOENIX CONTACT

## Terminal block for printed circuit board, rated current: ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MKDSN 1,5/10-5,08 BD:86-25

PRODUCT IMAGE\nNOT  
AVAILABLE

|                 |                                |
|-----------------|--------------------------------|
| Manufacturer    | PHOENIX CONTACT                |
| MPN / Reference | MKDSN 1,5/10-5,08 BD:86-25     |
| Catalog number  | 1704731                        |
| Category        | Printed circuit board terminal |
| Minimum order   | 40 Pcs                         |
| Document ID     | EO-6312E79595                  |
| Generated       | 2026-09-29                     |

## Product Overview

Terminal block for printed circuit board, rated current: 13.5 A, rated voltage: 400 V, pitch: 5.08 mm, number of poles: 10, connection type: Screw connection with traction capsule, mounting: Wave soldering, conductor/printed circuit board connection direction: 0 °, color: green

Terminal block for printed circuit board, nominal current: 13.5 A, nominal voltage (III/2): 400 V, nominal cross-section: 1.5 mm<sup>2</sup>, number of potentials: 10, number of rows: 1, number of poles per row: 10, article family: MKDSN 1.5, pitch: 5.08 mm, connection type: Screw connection with traction capsule, screw clamping method: L Longitudinal slot, mounting: Wave soldering, conductor/printed circuit board connection direction: 0 °, color: green, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.5 mm, number of solder pins per potential: 1, packaging type: boxed

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path PHOENIX CONTACT &gt; PCB Connectors (PCC)

## Additional Product Information

PCB terminal block, nominal current: 13.5 A, nom. voltage: 400 V, pitch: 5.08 mm, number of positions: 10, connection method: Screw connection with tension sleeve, mounting: Wave soldering, conductor/PCB connection direction: 0 °, color: green

Your advantages

Well-known connection principle allows worldwide useLow temperature rise, thanks to maximum contact forceAllows connection of two conductorsExtremely small design for the respective conductor cross sectionThe latching on the side enables various numbers of positions to be combinedKey Commercial Data

Orderkey 1704731

Packing unit 1

GTIN 4046356734066

Custom tariff number 85369010

Electrical parameters

Rated current 13.5 A

Rated insulation voltage (III/2) 400 V

Rated surge voltage (III/2) 4 kV

Connection capacity

Conductor cross section solid 0.14 mm<sup>2</sup> ... 1.5 mm<sup>2</sup>

Conductor cross section flexible 0.14 mm<sup>2</sup> ... 1.5 mm<sup>2</sup>

Conductor cross section AWG / kcmil 26 ... 16

Conductor cross section flexible, with ferrule without plastic sleeve 0.25 mm<sup>2</sup> ... 1 mm<sup>2</sup>

2 conductors with same cross section, solid 0.14 mm<sup>2</sup> ... 0.75 mm<sup>2</sup>

2 conductors with same cross section, flexible 0.14 mm<sup>2</sup> ... 0.75 mm<sup>2</sup>

2 conductors with same cross section, stranded, ferrules without plastic sleeve 0.25 mm<sup>2</sup> ... 0.5 mm<sup>2</sup>

2 conductors with same cross section, stranded, with TWIN ferrules with plastic sleeve 0.5 mm<sup>2</sup> ... 0.75 mm<sup>2</sup>

Stripping length 6 mm

Material data - contact

Note WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC JESD 201

Contac...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MKDSN 1,5/10-5,08 BD:86-25 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.