INDUSTRIAL COMPONENT DATA

PT 1,5/ 2-PVH-5,0-A YE BD:-151 1701837 PHOENIX CONTACT Plug

Brand: PHOENIX CONTACT | Manufacturer Part Number: PT 1,5/ 2-PVH-5,0-A YE BD:-151



Manufacturer	PHOENIX CONTACT
MPN / Reference	PT 1,5/ 2-PVH-5,0-A YE BD:-151
Catalog number	1701837
Category	Cable connector
Minimum order	250 Pcs
Document ID	EO-1605742BB7
Generated	2026-11-19

Product Overview

Plug

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data
Orderkey 1701837
Packing unit 250 pc
Minimum order quantity 250 pc
Note Made to Order (non-returnable)
GTIN 4046356562614
Weight per Piece (excluding packing) 2.270 g
Custom tariff number 85366990
Country of origin DE (Germany)
Dimensions
Length [l] 11.4 mm
Width [w] 10 mm
Height [h] 11.4 mm
Pitch 5 mm
Dimension a 5 mm

General
Range of articles PT 1,5/..-PVH-A
Number of positions 2
Connection method Screw connection with wire protector
Rated voltage (III/3) 250 V
Connection in acc. with standard EN-VDE
Nominal current IN 12 A
Nominal cross section 1.5 mm²
Connection data
Conductor cross section solid min. 0.2 mm²
Conductor cross section solid max. 2.5 mm²
Conductor cross section flexible min. 0.2 mm²
Conductor cross section flexible max. 2.5 mm²
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 1.5 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule with plastic sleeve max. 1.5 mm²
Conductor cross section AWG min. 26
Conductor cross section AWG max. 14
2 conductors with same cross section, solid min. 0.2 mm²
2 conductors with same cross section, solid max. 0.75 mm²
2 conductors with same cross section, stranded min. 0.2 mm²
2 conductors with same cross section, stranded max. 0.75 mm²
2 conductors with same cross section, stranded, ferrules without plastic sleeve,....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PT 1,5/ 2-PVH-5,0-A YE BD:-151 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.