
INDUSTRIAL COMPONENT DATA

MSTBV 2,5/ 5-GF-5,08 GYPA1,3,5 1701377 PHOENIX CONTACT Feed-through header

Brand: PHOENIX CONTACT | Manufacturer Part Number: MSTBV 2,5/ 5-GF-5,08 GYPA1,3,5



Manufacturer	PHOENIX CONTACT
MPN / Reference	MSTBV 2,5/ 5-GF-5,08 GYPA1,3,5
Catalog number	1701377
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-62E23BE09F
Generated	2026-11-19

Product Overview

Feed-through header
Printed circuit board base housing, nominal section: 2.5 mm², color: gray, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Male, number of potentials: 3, number of rows: 1, number of poles: 5, number of connections: 3, family of articles: MSTBV 2.5/.. -GF, pitch: 5.08 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 3.9 mm, number of solder pins per potential: 1, plug-in system: COMBICON MSTB 2.5, Plug-in face orientation: Standard, locking: Screw lock, fixing type: Air clamping (thread), packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data
Orderkey 1701377
Packing unit 1
GTIN 4046356529433
Custom tariff number 85366930
Dimensions
Length [l] 8.57 mm
Width 35.56 mm
Pitch 5.08 mm
Dimension a 20.32 mm

Width [w] 35.56 mm
Height [h] 15.9 mm
Height 12 mm
Length of the solder pin 3.9 mm
Pin dimensions 1 x 1 mm
Length 8.57 mm
General
Range of articles MSTBV 2,5/..-GF
Rated voltage (III/3) 250 V
Connection in acc. with standard EN-VDE
Nominal current IN 12 A
Color gray
Number of positions 5
Standards and Regulations
Connection in acc. with standard EN-VDE
CUL
Environmental Product Compliance
REACh SVHC Lead 7439-92-1
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab “Downloads”, Category “Manufacturer's declaration”
Classifications
eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss 7.027440402eCl@ss 8.027440402eCl@ss 9.027440402
ETIM 3.0EC001121ETIM 4.0EC002637ETIM 5.0EC002637ETIM 6.0EC002637
UNSPSC 6.0130211810UNSPSC 7.090139121409UNSPSC 1139121409UNSPSC 12.0139121409UNSPSC 13.239121409

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MSTBV 2,5/ 5-GF-5,08 GYPA1,3,5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.