
INDUSTRIAL COMPONENT DATA

MSTBVA 2,5/ 3-G-5,08 BK PA13 1747067 PHOENIX CONTACT Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: MSTBVA 2,5/ 3-G-5,08 BK PA13



Manufacturer	PHOENIX CONTACT
MPN / Reference	MSTBVA 2,5/ 3-G-5,08 BK PA13
Catalog number	1747067
Category	Printed circuit board connector
Minimum order	1000 Pcs
Document ID	EO-231D38DCD3
Generated	2026-11-19

Product Overview

Printed-circuit board connector
Printed circuit board base housing, nominal section: 2.5 mm², color: black, nominal current: 12 A, dimensioning voltage (III/2): 320 V, contact surface: Tin, contact type: Male, number of potentials: 3, number of rows: 1, number of poles: 3, number of connections: 3, family of articles: MSTBVA 2.5/.. -G, pitch: 5.08 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 3.9 mm, number of solder pins per potential: 1, plug-in system: CLASSIC COMBICON, Plug-in face orientation: Standard, Locking: without, fixing type: without, packaging type: boxed PCB headers, nominal current: 12 A, rated voltage (III/2): 320 V, nominal cross section: 2.5 mm², number of positions: 3, pitch: 5.08 mm, color: black, contact surface: Tin, mounting: Wave soldering, pin layout: Linear pinning, solder pin [P]: 3.9 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data
Orderkey 1747067
Packing unit 1 pc
Minimum order quantity 50 pc
GTIN 4046356295277
Weight per Piece (excluding packing) 1.620 g
Custom tariff number 85366930

Country of origin DE (Germany)
Drawings
General
Environmental Product Compliance
Dimensions
Standards and Regulations
Classifications
Drawings
Diagram
Type: MSTB 2,5/...-ST-5,08 with MSTBVA 2,5/...-G-5,08
Diagram
Type: FKCN 2,5/...-ST-5,08 with MSTBVA 2,5/...-G-5,08
Diagram
Type: TFKC 2,5/...-ST-5,08 with MSTBVA 2,5/...-G-5,08
Diagram
Type: TVMSTB 2,5/...-ST-5,08 with MSTBVA 2,5/...-G-5,08
Diagram
Type: MSTBP 2,5/...-ST-5,08 with MSTBVA 2,5/...-G-5,08
Diagram
Type: FRONT-MSTB 2,5/...-ST-5,08 with MSTBVA 2,5/...-G-5,08
Diagram
Type: MVSTB(R/W) 2,5/...-ST-5,08 with MSTBVA 2,5/...-G-5,08
Diagram
Type: SMSTB 2,5/...-ST-5,08 with MSTBVA 2,5/...-G-5,08
Diagram
Type: FKCVR 2,5/...-ST-5,08 with MSTBVA 2,5/...-G-5,08
Diagram
Type: FKCVW 2,5/...-ST-5,08 with MSTBVA 2,5/...-G-5,08
Diagram
Type: FKCT 2,5/...-ST-5,08 with MSTBVA 2,5/...-G-5,08
Back to topDimensions
Length [l] 8.57 mm
Width 17.24 mm
Pitch 5.08 mm
Dimension a 10.16 mm
Width [w] 17.24 mm
Height [h] 15.9 mm
Height 12 mm
Length of the solder pin 3.9 mm
Pin dimensions 1 x 1 mm
Length 8.57 mm
Back to topGeneral
Range of articles MSTBVA 2,5/..-G
Rated voltage (III/3) 250 V
Connection in acc. with standard EN-VDE
Nominal current IN 12 A
Color black

Number of positions 3
Back to topStandards and Regulations
Connection in acc. with standard EN-VDE
CSA...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MSTBVA 2,5/ 3-G-5,08 BK PA13 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.