INDUSTRIAL COMPONENT DATA

MSTBVK 2,5/12-STF-5,08 1849189 PHOENIX CONTACT Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: MSTBVK 2,5/12-STF-5,08



Manufacturer	PHOENIX CONTACT
MPN / Reference	MSTBVK 2,5/12-STF-5,08
Catalog number	1849189
Category	Feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-554D2C1BF9
Generated	2026-11-19

Product Overview

Printed-circuit board connector
Rail connector, nominal section: 2.5 mm², color: green, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Female, number of potentials: 12, number of rows: 1, number of poles: 12, number of connections: 12, family of articles: MSTBVK 2.5/.. -STF, pitch: 5.08 mm, connection type: Screw connection with traction capsule, screw clamping form: L Longitudinal slot, mounting: Rail, driver/printed circuit board connection direction: 0 °, plug-in system: COMBICON MSTB 2.5, lock: Screw lock, fixing type: Air clamping (screw), packaging type: boxed
Connector on the profile, nominal cross-section: 2.5 mm2, colour: green, nominal current: 12 A, reference voltage (III/2): 320 V, contact area: Sn, contact type: Female connector, number of potentials: 12, number of rows: 1, number of poles: 12, number of connections: 12, item range: MSTBVK 2.5/.. -STF, pitch: 5.08 mm, connection type: Screw connection with ring, screw driving surface: L Longitudinal slot, conductor/PCB mating direction: 0 °, Plug-in system: COMBICON MSTB 2.5, Locking: Screw lock, Fastening type: Screw flange, Packaging type: Packed in carton

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data
Orderkey 1849189
Packing unit 50 pc
Catalog page Page 213 (CC-2002)
GTIN 4017918105679

Weight per Piece (excluding packing) 30.200 g
Custom tariff number 85366990
Country of origin DE (Germany)
Dimensions
Pitch 5.08 mm
Dimension a 55.88 mm
General
Range of articles MSTBVK 2,5/..-STF
Number of positions 12
Connection method Screw connection with tension sleeve
Insulating material group I
Rated surge voltage (III/3) 4 kV
Rated surge voltage (III/2) 4 kV
Rated surge voltage (II/2) 4 kV
Rated voltage (III/3) 320 V
Rated voltage (III/2) 320 V
Rated voltage (II/2) 630 V
Connection in acc. with standard EN-VDE
Nominal current IN 12 A
Nominal cross section 2.5 mm²
Maximum load current 12 A
Insulating material PA
Flammability rating according to UL 94 V0
Internal cylindrical gage A3
Stripping length 7 mm
Screw thread M3
Tightening torque, min 0.5 Nm
Tightening torque max 0.6 Nm
Connection data
Conductor cross section solid min. 0.2 mm²
Conductor cross section solid max. 2.5 mm²
Conductor cross section flexible min. 0.2 mm²
Conductor cross section flexible max. 2.5 mm²
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 2.5 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule with plastic sleeve max. 2.5 mm²
Conductor cross section AWG min. 24
Conductor cross section AWG max. 12
2 c...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MSTBVK 2,5/12-STF-5,08 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.