INDUSTRIAL COMPONENT DATA

MUTTB 2,5-BE 1066350 PHOENIX CONTACT Mini-terminal block, for mounting self-selectable components, nominal v..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MUTTB 2,5-BE



Manufacturer	PHOENIX CONTACT
MPN / Reference	MUTTB 2,5-BE
Catalog number	1066350
Category	Component terminal block
Minimum order	50 Pcs
Document ID	EO-00B9AE48F5
Generated	2026-11-18

Product Overview

Mini-terminal block, for mounting self-selectable components, nominal voltage: 500 V, nominal current: 22 A, connection type: Screw connection, Sizing cross-section: 2.5 mm², cross-section: 0.2 mm² - 4 mm², mounting: NS 15, NS 35/7.5, NS 35/15, color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs

Additional Product Information

Technical dataItem PropertiesProduct Type Miniterminal
Number of poles 2
Number of connections 4
Number of rows 2
Insulation Properties
Surge Category Iii
Degree of pollution 3
Electrical PropertiesMaximum Dissipated Power with Nominal Condition 0.77 W
Connection dataNumber of connections per floor 2
Nominal Section 2.5 mm²
AWG Conductor Section (Converted according to IEC)
Screw thread M3
Tightening torque 0,5 ... 0.6 Nm

Length to be de-insulated 7 mm
7 mm ... 9 mm
Male Gauge A3
Standard-compliant connection IEC 60947-7-1
Rigid conductor section 0.2 mm² ... 4 mm²
AWG Conductor Section 24 ... 12 (Converted according to IEC)
Flexible conductor section 0.2 mm² ... 2.5 mm²
Flexible Wire Section [AWG] 4 ... 14 (Converted according to IEC)
Flexible cable section (toe cap without plastic sleeve) 0.25 mm² ... 2.5 mm²
Flexible cable section (toe cap with plastic sleeve) 0.25 mm² ... 2.5 mm²
2 conductors with the same cross-section, rigid 0.2 mm² ... 1.5 mm²
2 conductors with the same rigid AWG cross-section 24 ... 16 (Converted according to IEC)
2 conductors with the same cross-section, flexible 0.2 mm² ... 1.5 mm²
2 conductors with the same flexible AWG cross-section 24 ... 16 (Converted according to IEC)
2 conductors of equal cross-section, flexible with toe cap, without plastic sleeve 0.2 mm² ... 1.5 mm²
2 conductors with the same cross-section, flexible with TWIN toe cap with plastic sleeve 0.5 mm² ... 1.5 mm²
Nominal current 22 A (with a conductor cross-section of 2.5 mm²)
Maxi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MUTTB 2,5-BE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.