INDUSTRIAL COMPONENT DATA

# Q 1,5/2FS/11-11KU-ESAX 1640359 PHOENIX CONTACT Connector set

**Brand: PHOENIX CONTACT | Manufacturer Part Number: Q 1,5/2FS/11-11KU-ESAX**

PRODUCT IMAGE\nNOT AVAILABLE

| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | Q 1,5/2FS/11-11KU-ESAX |
| Catalog number | 1640359 |
| Category | Sensor-actuator connector chassis |
| Minimum order | 10 Pcs |
| Document ID | EO-ECCEE3FB13 |
| Generated | 2026-11-19 |

## Product Overview

Connector set

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > QUICKON Installation System (QPD) |

## Additional Product Information

Key Commercial Data
Orderkey 1640359
Packing unit 10 pc
Minimum order quantity 10 pc
Note Made to Order (non-returnable)
GTIN 4017918435769
Weight per Piece (excluding packing) 19.170 g
Custom tariff number 85369010
Country of origin PL (Poland)
General
Connection If the conductor is reconnected, it must be cut off above the last contact point. QUICKON components may only be operated when under no load.
Color green
Connection method QUICKON connection
Number of positions 2

Number of connections 2
Cabel
Structure of individual litz in acc. with VDE 0295 / smallest wire diameter VDE 0295 Cl.2-5, min. wire diameter 0.2 mm
Wire diameter including insulation >= 3 mm
Ambient conditions
Degree of protection IP65
IP67
Electrical characteristics
Nominal current IN 17.5 A
Rated voltage (III/3) 250 V
Note on the rated voltage (III/3) with insulating sleeve
Mechanical characteristics
QUICKON connectability 10 (if the conductor is connected more than once, seal and cap may need to be replaced.)
Material data
Contact material Copper alloy
Contact surface material Pre-nickel plated and tin-plated
Contact carrier material PA 6.6
Flammability rating according to UL 94 V0
Overvoltage category III
Degree of pollution 3
Standards and Regulations
Flammability rating according to UL 94 V0
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Classifications
eCl@ss 4.027140815eCl@ss 4.127140815eCl@ss 5.027...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / Q 1,5/2FS/11-11KU-ESAX with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.