

INDUSTRIAL COMPONENT DATA

ZFK3DSA 1,5-5,08- 3 GY7035 1773934 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: ZFK3DSA 1,5-5,08-3 GY7035



Manufacturer	PHOENIX CONTACT
MPN / Reference	ZFK3DSA 1,5-5,08-3 GY7035
Catalog number	1773934
Category	Printed circuit board terminal
Minimum order	50 Pcs
Document ID	EO-96ECF3D2C8
Generated	2026-09-29

Product Overview

PCB terminal block

Printed circuit board terminal block, rated current: 12 A, rated voltage (III/2): 400 V, rated cross-section: 1.5 mm², number of potentials: 9, number of rows: 3, number of poles per row: 3, article family: ZFK3DS(A) 1.5, pitch: 5.08 mm, connection type: Spring connection, mounting: Wave soldering, conductor connection direction/printed circuit board: 45 °, color: light gray, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.4 mm, number of solder pins per potential: 1, packaging type: boxed

PCB terminal, nominal current: 12 A, reference voltage (III/2): 400 V, nominal cross-section: 1.5 mm², number of potentials: 9, number of rows: 3, number of poles per row: 3, item range: ZFK3DS(A) 1.5, pitch: 5.08 mm, connection type: Spring connection, mounting: Wave soldering, conductor/PCB plugging direction: 45°, colour: light grey, Pin layout: Linear broaching, Spindle length [P]: 3.4 mm, Number of pins per potential: 1, Packaging type: Packed in carton

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 1773934

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

GTIN 4046356476591

Weight per Piece (excluding packing) 14.560 g

Custom tariff number 85369010

Country of origin DE (Germany)

Item properties

Brief article description PCB terminal block

Range of articles ZFK3DS(A) 1,5

Pitch 5.08 mm

Number of positions 3

Connection method Spring-cage connection

Mounting type Wave soldering

Pin layout Linear pinning

Number of levels 3

Number of connections 9

Number of potentials 9

Electrical parameters

Rated current 12 A

Rated insulation voltage (III/2) 400 V

Rated surge voltage (III/2) 4 kV

Connection capacity

Conductor cross section solid 0.2 mm² ... 2.5 mm²

Conductor cross section flexible 0.2 mm² ... 1.5 mm²

Conductor cross section AWG / kcmil 24 ... 14

Conductor cross section flexible, with ferrule without plastic sleeve 0.25 mm² ... 1.5 mm²

Conductor cross section, flexible, with ferrule, with plastic sleeve 0.25 mm² ... 1.5 mm²

Stripping length 7.5 mm

Material data - contact

Note WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC JESD 201

Contact material Cu alloy

Surface characteristics hot-dip tin-plated

Metal surface terminal point (top layer) Tin (10 - 16 µm Sn)

Metal surface soldering area (top layer) Tin (10 - 16 µm Sn)

Material data - housing

Insulating material PA

Insulating material group I

CTI according to IEC 60112 600

Flammability rating according to UL 94 V0

Glow wire flammability in...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ZFK3DSA 1,5-5,08-3 GY7035 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.