INDUSTRIAL COMPONENT DATA

MVSTBU 2,5/12-STF BK 1783795 PHOENIX CONTACT Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: MVSTBU 2,5/12-STF BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	MVSTBU 2,5/12-STF BK
Catalog number	1783795
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-0FDC0BAB7D
Generated	2026-11-19

Product Overview

Printed-circuit board connector
Direct plug-in block, nominal section: 2.5 mm², color: black, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Female, number of potentials: 12, number of rows: 1, number of poles: 12, number of connections: 12, family of articles: MVSTBU 2.5/.. -STF, pitch: 5 mm, connection type: Screw connection with traction capsule, screw clamping form: L Longitudinal slot, mounting: Direct mounting, connection direction driver/printed circuit board: 0 °, clamping hook: - without clamping hook, plug-in system: COMBICON MSTB 2.5, locking: Screw lock, fixing type: Air clamping (screw), Packaging Type: Boxed Packaging

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data
Orderkey 1783795
Packing unit 50 pc
Note Made to Order (non-returnable)
GTIN 4017918217990
Weight per Piece (excluding packing) 23.700 g
Custom tariff number 85366990
Country of origin DE (Germany)
Dimensions

Length [l] 22.1 mm
Width [w] 69.8 mm
Height [h] 17 mm
Pitch 5 mm
Dimension a 55 mm
General
Range of articles MVSTBU 2,5/..-STF
Number of positions 12
Connection method Screw connection with tension sleeve
Nominal cross section 2.5 mm²
Standards and Regulations
Connection in acc. with standard CSA
Environmental Product Compliance
REACh SVHC Lead 7439-92-1
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab “Downloads”, Category “Manufacturer's declaration”
Classifications
eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127141100eCl@ss 6.027141100eCl@ss 7.027141106eCl@ss 8.027440309eCl@ss 9.027440309
ETIM 3.0EC001121ETIM 4.0EC002637ETIM 5.0EC002638ETIM 6.0EC001284
UNSPSC 6.0130211810UNSPSC 7.090139121409UNSPSC 1139121409UNSPSC 12.0139121409UNSPSC 13.239121409

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MVSTBU 2,5/12-STF BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.