
INDUSTRIAL COMPONENT DATA

# MVSTBW 2,5/20-ST AU 1741999 PHOENIX CONTACT Printed-circuit board connector

**Brand: PHOENIX CONTACT | Manufacturer Part Number: MVSTBW 2,5/20-ST AU**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | MVSTBW 2,5/20-ST AU |
| Catalog number | 1741999 |
| Category | Cable connector |
| Minimum order | 50 Pcs |
| Document ID | EO-9CEADE0F47 |
| Generated | 2026-11-19 |

## Product Overview

Printed-circuit board connector
Connector for printed circuit board, nominal section: 2.5 mm², color: green, nominal current: 12 A, contact surface: Gold, contact type: Female connection, Number of potentials: 20, Number of rows: 1, Number of poles per row: 20, number of connections: 20, family of articles: MVSTBW 2.5/.. -ST, pitch: 5 mm, connection type: Screw connection with traction capsule, connection direction conductor/printed circuit board: -90 °, Stecksystem: CLASSIC COMBICON, Lock: without, packaging type: boxed

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > PCB Connectors (PCC) |

## Additional Product Information

Key Commercial Data
Orderkey 1741999
Packing unit 50 pc
Note Made to Order (non-returnable)
GTIN 4017918220495
Weight per Piece (excluding packing) 38.320 g
Custom tariff number 85366990
Country of origin DE (Germany)
Dimensions
Length [ l ] 12.5 mm

Width [ w ] 100 mm
Height [ h ] 26 mm
Pitch 5 mm
Dimension a 95 mm
General
Range of articles MVSTBW 2,5/..-ST
Number of positions 20
Connection method Screw connection with tension sleeve
Insulating material group I
Rated surge voltage (III/3) 4 kV
Rated surge voltage (III/2) 4 kV
Rated surge voltage (II/2) 4 kV
Rated voltage (III/3) 320 V
Rated voltage (III/2) 320 V
Rated voltage (II/2) 630 V
Connection in acc. with standard EN-VDE
Nominal current IN 12 A
Nominal cross section 2.5 mm²
Maximum load current 12 A
Insulating material PA
Flammability rating according to UL 94 V0
Internal cylindrical gage A3
Stripping length 7 mm
Screw thread M3
Tightening torque, min 0.5 Nm
Tightening torque max 0.6 Nm
Connection data
Conductor cross section solid min. 0.2 mm²
Conductor cross section solid max. 2.5 mm²
Conductor cross section flexible min. 0.2 mm²
Conductor cross section flexible max. 2.5 mm²
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 2.5 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule with plastic sleeve max. 2.5 mm²
Conductor cross sec...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MVSTBW 2,5/20-ST AU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.