INDUSTRIAL COMPONENT DATA

NBC-M12MS/15,0-94B/M12FS VA 1063380 PHOENIX CONTACT Network cable, Ethernet CAT5 (1 Gbps), 8-position, PUR, ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: NBC-M12MS/15,0-94B/M12FS VA

PRODUCT IMAGE\nNOT AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	NBC-M12MS/15,0-94B/M12FS VA
Catalog number	1063380
Category	Sensor-actuator patch cord
Minimum order	100 Pcs
Document ID	EO-FB59657C5C
Generated	2026-11-19

Product Overview

Network cable, Ethernet CAT5 (1 Gbps), 8-position, PUR, water blue RAL 5021, shielded, Plug straight M12 / IP67, coding: A, on Socket M12, cable length: 1 m
Network cable, CAT5 Ethernet (1 GBit/s), 8-pole, PUR, water blue RAL5021, shielded, M12 straight connector, encoding: A / IP67, to M12 female, cable length: 1 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data
Orderkey 1063380
Packing unit 1
GTIN 4055626719627
Custom tariff number 85444290
Dimensions
Characteristics head 1
Environmental Product Compliance
General data
Characteristics head 2
Classifications
Dimensions

Length of cable 1 m
Back to topGeneral data
Number of positions 8
Signal type/category Ethernet CAT5, 1 Gbps
Back to topCharacteristics head 1
Head type Plug straight M12 / IP67
No. of positions (pin connector pattern) 8
Coding A (Standard)
Color black
Material (component) CuZn (Contact)
TPU, hardly inflammable, self-extinguishing (Grip)
Zinc die-cast, nickel-plated (Screw connection)
Insulation resistance >= 100 M?
Insertion/withdrawal cycles >= 100
Torque 0.4 Nm
Ambient temperature (operation) -25 °C ... 90 °C
Back to topCharacteristics head 2
Head type Socket M12
Back to topEnvironmental Product Compliance
REACh SVHC
Lead 7439-92-1
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab “Downloads”, Category “Manufacturer's declaration”
Back to topClassifications
eCl@ss
eCl@ss 4.0 27060307
eCl@ss 4.1 27060307
eCl@ss 5.0 27060307
eCl@ss 5.1 27060307
eCl@ss 6.0 27060307
eCl@ss 7.0 27060308
eCl@ss 8.0 27279218
eCl@ss 9.0 27060308
Back to topETIM
ETIM 3.0 EC000830
ETIM 4.0 EC001855
ETIM 5.0 EC001855
ETIM 6.0 EC001262
ETIM 7.0 EC001262
Back to topUNSPSC
UNSPSC 6.01 31261501
UNSPSC 7.0901 31261501
UNSPSC 11 31261501
UNSPSC 12.01 31261501
UNSPSC 13.2 31251501
UNSPSC 18.0 26121604
UNSPSC 19.0 26121604

UNSPSC 20...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / NBC-M12MS/15,0-94B/M12FS VA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.