INDUSTRIAL COMPONENT DATA

NBC-MRD/ 0,5-93E/FRD SCO US 1408739 PHOENIX CONTACT Network cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: NBC-MRD/ 0,5-93E/FRD SCO US



Manufacturer	PHOENIX CONTACT
MPN / Reference	NBC-MRD/ 0,5-93E/FRD SCO US
Catalog number	1408739
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-B32379C625
Generated	2026-11-19

Product Overview

Network cable
Network cable, CAT5 Ethernet (100 MBit/s), 4-pole halogen-free, shielded, M12 angled connector, encoding: D/IP67, to M12 angled female, encoding: D/IP67, cable length: 0.5 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data
Orderkey 1408739
Packing unit 1 pc
Minimum order quantity 50 pc
Note Made to Order (non-returnable)
GTIN 4046356828666
Weight per Piece (excluding packing) 22.220 g
Custom tariff number 85444210
Country of origin US (United States)
Dimensions
Length of cable 0.5 m
Ambient conditions
Degree of protection IP65

IP67
Ambient temperature (operation) -25 °C ... 85 °C (M12 connector)
General data
Rated current at 40°C 4 A (Plug/socket in accordance with IEC 61076-2-101, cable technical data is to be observed)
Rated voltage 48 V AC
60 V DC
Number of positions 4
Signal type/category Ethernet CAT5 (IEC 11801), 100 Mbps
Standards/regulations M12 connector IEC 61076-2-101
Contact material CuSn
Contact carrier material TPU GF
Contact surface material Ni/Au
Characteristics head 1
Head type Plug angled M12 SPEEDCON / IP67
Coding D (Data)
Characteristics head 2
Head type Socket angled M12 SPEEDCON / IP67
Coding D (Data)
Color black
Standards and Regulations
Standard designation M12 connector
Standards/regulations IEC 61076-2-101
Cable
Cable type PUR ETHERNET 2x2 FLEX
Cable type (abbreviation) 93E
UL AWM style 20963 (80°C/30 V)
Signal type/category Ethernet CAT5 (IEC 11801), 100 Mbps
Cable structure 2x2xAWG26/7; SF/UTP
Conductor cross section 2x 2x 0.14 mm²
AWG signal line 26
Conductor structure signal line 7x 0.16 mm
Core diameter including insulation 0.98 mm
Wire colors white/orange-orange, white/green-green
Twisted pairs 2 cores to the pair
Overall twist Two pairs with...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / NBC-MRD/ 0,5-93E/FRD SCO US with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.