INDUSTRIAL COMPONENT DATA

NBC-MSD/ 100,0-93R/R4AC SCO 1423607 PHOENIX CONTACT Network cable NBC-MSD/ 100,0-93R/R4AC SCO 1423607

Brand: PHOENIX CONTACT | Manufacturer Part Number: NBC-MSD/ 100,0-93R/R4AC SCO



Manufacturer	PHOENIX CONTACT
MPN / Reference	NBC-MSD/ 100,0-93R/R4AC SCO
Catalog number	1423607
Category	Patch cord copper (twisted pair)
Minimum order	5 Pcs
Document ID	EO-05513DC04C
Generated	2026-11-19

Product Overview

Network cable - NBC-MSD/ 100,0-93R/R4AC SCO - 1423607
Network cable, PROFINET CAT5 (100 MBit/s), 4-pole, shielded, M12 straight connector, coding: D SPEEDCON / IP67, a RJ45 / IP20 straight connector, cable length: 100 m
Network cable, PROFINET CAT5 (100 Mbit/s), 4-pin, halogen-free, green RAL 6018, shielded, straight male M12 SPEEDCON, coding: D / IP67, on straight male RJ45 / IP20, cable length: 100 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Network cable, PROFINET CAT5 (100 Mbps), 4-position, PUR/PVC, green RAL 6018, shielded, Plug straight M12 SPEEDCON / IP67, coding: D, on Plug straight RJ45 / IP20, cable length: 100 m
Key Commercial Data
Orderkey 1423607
Packing unit 1
GTIN 4055626347370
Custom tariff number 85444290
Dimensions
Length of cable 100 m
Ambient conditions
Ambient temperature (operation) -25 °C ... 90 °C (M12 connector)

-25 °C ... 80 °C (RJ45 connector)
General data
Note This product corresponds to the PROFINET Cabling and Interconnection Technology Guideline for PROFINET regulations, version 2.00, order no: 2.252, Chapter 8.2 Connectors for Outside Environment (Balanced cabling)
Rated current at 40°C 1 A
Rated voltage 48 V AC
60 V DC
Number of positions 4
Signal type/category PROFINET CAT5 (IEC 11801), 100 Mbps
Standards/regulations M12 connector IEC 61076-2-101
Contact material CuSn
Contact carrier material TPU GF
Contact surface material Ni/Au
Housing material Plastic
Characteristics head 1
Head type Plug straight M12 SPEEDCON / IP67
No. of positions (pin connector pattern) 4
Coding D (Data)
Color black
Material (component) CuSn (Contact)
Ni/Au (Contact surface)
PA (Contact carriers)
TPU, hardly inflammable, self-extinguishing (Grip)
Zinc die-cast, nickel-plated (Screw connection)
Insulation resistance >= 100 M?
Insertion/withdrawal cycles >= 100
Torque 0.4 Nm
Ambient temperature (operation) -25 °C ... 90 °C
Characteristics head 2
Head type Plug straight RJ45 / IP20
No. of positions (pin connect...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / NBC-MSD/ 100,0-93R/R4AC SCO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.