INDUSTRIAL COMPONENT DATA

NBC-M12MSD/20,0-93E/M12MSD 1426517 PHOENIX CONTACT Network Cable NBC-MSD/20,0-93E/MSD SCO 1426517

Brand: PHOENIX CONTACT | Manufacturer Part Number: NBC-M12MSD/20,0-93E/M12MSD

PRODUCT IMAGE\nNOT AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	NBC-M12MSD/20,0-93E/M12MSD
Catalog number	1426517
Category	Sensor-actuator patch cord
Minimum order	10 Pcs
Document ID	EO-8B2F66CEFA
Generated	2026-11-18

Product Overview

Network Cable - NBC-MSD/20,0-93E/MSD SCO - 1426517
Network cable, CAT5 Ethernet (100 MBit/s), 4-pole, shielded (Advanced Shielding Technology), M12 straight connector, encoding: D / IP67, to M12 straight connector, encoding: D / IP67, cable length: 20 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Network Cable, Ethernet CAT5 (100 MBit/s), 4-pole, PUR, aqua blue RAL 5021, shielded, Plug straight M12 SPEEDCON / IP67, coding: D, on Plug straight M12 SPEEDCON / IP67, coding: D, cable length: 20 m
Data commercial
Key order One million four hundred twenty six thousand five hundred seventeen
Packing unit 1 pcs
Key selling BF1CJI -
Minimum order quantity 50 pcs
EAN Four trillion fifty five billion six hundred twenty six million four hundred sixty two thousand two hundred fifty seven
Unit weight (excluding packaging) 870,400 g
Tariff number tariff Eighty five million four hundred forty four thousand two hundred ninety
Measures
Cable length 20 m
General data

Tension sizing 48 V AC
60 V DC
Number of poles Four
Signal type/category CAT5 Ethernet, 100 MBit/s
Values nominal head 1
Construction header Connector straight M12 SPEEDCON / IP67
Number of poles (face of plug) Four
Encoding D (Data)
Color black
Material (components) CuZn (Contact)
Insulation resistance >= 100 M?
Cycles of plug >= 100
Tightening torque 0.4 Nm
Room temperature (service) -25 °C ... 90 °C
Nominal values 2 head
Construction header Connector straight M12 SPEEDCON / IP67
Number of poles (face of plug) Four
Encoding D (Data)
Color black
Material (components) CuZn (Contact)
Ni/Au (Surface contacts)
PA (Support contacts)
TPU, low flammability, self-extinguishing (Body grip)
Die-cast zinc, nickel-Connection by screw)
Insulation resistance >= 100 M?
Cycles of plug >= 100
Room temperature (service) -25 °C ... 90 °C
Enviro...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / NBC-M12MSD/20,0-93E/M12MSD with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.