INDUSTRIAL COMPONENT DATA

NBC-MSD/ 7,5-93K/MSD SCO 1412422 PHOENIX CONTACT Network cable NBC-MSD/ 7,5-93K/MSD SCO 1412422

Brand: PHOENIX CONTACT | Manufacturer Part Number: NBC-MSD/ 7,5-93K/MSD SCO



Manufacturer	PHOENIX CONTACT
MPN / Reference	NBC-MSD/ 7,5-93K/MSD SCO
Catalog number	1412422
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-DC807020D6
Generated	2026-11-18

Product Overview

Network cable - NBC-MSD/ 7,5-93K/MSD SCO - 1412422
Network cable, Sercos CAT5 (100 MBit/s), 4-pole, shielded, M12 straight connector, encoding: D SPEEDCON / IP67, to M12 straight connector, coding: D SPEEDCON / IP67, cable length: 7.5 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Network cable, Sercos CAT5 (100 Mbps), 4-position, PVC/PVC, signal red RAL 3020, shielded, Plug straight M12 SPEEDCON / IP67, coding: D, on Plug straight M12 SPEEDCON / IP67, coding: D, cable length: 7.5 m
Key Commercial Data
Orderkey 1412422
Packing unit 1
GTIN 4046356960403
Custom tariff number 85444290
Dimensions
Length of cable 7.5 m
Ambient conditions
Degree of protection IP65 (M12 connector)
IP67 (M12 connector)
Ambient temperature (operation) -25 °C ... 90 °C (M12 connector)

General data
Rated current at 40°C 4 A
Rated voltage 48 V AC
60 V DC
Number of positions 4
Signal type/category Sercos CAT5 (IEC 11801), 100 Mbps
Standards/regulations M12 connector IEC 61076-2-101
Characteristics head 1
Head type Plug straight M12 SPEEDCON / IP67
No. of positions (pin connector pattern) 4
Coding D (Data)
Color black
Material (component) CuSn (Contact)
Ni/Au (Contact surface)
PA (Contact carriers)
TPU, hardly inflammable, self-extinguishing (Grip)
Zinc die-cast, nickel-plated (Screw connection)
Insulation resistance >= 100 M?
Insertion/withdrawal cycles >= 100
Torque 0.4 Nm
Ambient temperature (operation) -25 °C ... 90 °C
Characteristics head 2
Head type Plug straight M12 SPEEDCON / IP67
No. of positions (pin connector pattern) 4
Coding D (Data)
Color black
Material (component) CuSn (Contact)
Ni/Au (Contact surface)
Zinc die-cast, nickel-plated (Screw connection)
Zinc die-cast, nickel-plated (Screw connection)
TPU, hardly inflammable, self-extinguishing (Grip)
PA (Contact carriers)....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / NBC-MSD/ 7,5-93K/MSD SCO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES
Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.