INDUSTRIAL COMPONENT DATA

NBC-P12MRD/ 0,3-93E/P12FRD 1224273 PHOENIX CONTACT Network cable, CAT5 Ethernet (100 MBit/s), 4-pole, haloge..

Brand: PHOENIX CONTACT | Manufacturer Part Number: NBC-P12MRD/ 0,3-93E/P12FRD



Manufacturer	PHOENIX CONTACT
MPN / Reference	NBC-P12MRD/ 0,3-93E/P12FRD
Catalog number	1224273
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-36847EFBCB
Generated	2026-11-18

Product Overview

Network cable, CAT5 Ethernet (100 MBit/s), 4-pole, halogen-free PUR, water blue RAL 5021, shielded (Advanced Shielding Technology), Cranked connector M12 Push-pull, coding: D / IP67, to Elbowed Female M12 Push-pull, coding: D / IP67, cable length: 0.3 m
Network cable, Ethernet CAT5 (100 MBit/s), 4-pole, shielded (Advanced Shielding Technology), M12 angled connector, coding: D Push-pull / IP67, a M12 angled female, coding: D Push-pull / IP67, cable length: 0.3 m
Network cable, Ethernet CAT5 (100 Mbps), 4-position, shielded (Advanced Shielding Technology), Plug angled M12 Push Pull, coding: D / IP67, on Socket angled M12 Push Pull, coding: D / IP67, cable length: 0.3 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Technical dataProduct propertiesProduct type Data cable preassembled
Sensor type Ethernet
Number of positions 4
Application Standard
Shielded yes
InterfacesBus system Ethernet
Signal type/category Ethernet CAT5 (IEC 11801), 100 Mbps
SignalingStatus display No
Status display present No

Electrical propertiesNominal voltage UN 48 V AC
60 V DC
Nominal current IN 1.5 A
Transmission medium Copper
Transmission characteristics (category) CAT5 (IEC 11801:2002)
ConnectorConnection 1
Type Plug angled M12 Push Pull / IP67
Number of positions 4
Locking type Push Pull
Coding type D (Data)
Handle color black
Flammability rating according to UL 94 V0
Material CuSn (Contact)
Ni/Au (Contact surface)
PA (Contact carriers)
TPU, hardly inflammable, self-extinguishing (Grip)
Zinc die-cast, nickel-plated (Screw connection)
FKM (Seal)
Insertion/withdrawal cycles >= 100
Contact resistance <= 5 m?
Insulation resistance >= 100 M?
Overvoltage category II
Degree of pollution 3
Degree of protection IP67
Ambient temperature (operation) -25 °C ... 85 °C
Connection 2
Type Socket angled M12 Push Pull / IP67
Number of positions 4
Locking type Push Pull
Coding type D (Data)
Handle color black
Flammability rating according to UL 94 V0
Material CuSn (Contact)
Ni/Au (Contact surface)
PA (Contact carriers)
TPU, hardly inflammable, self-extinguishing (Grip)
Zinc die-cast, nickel-plated (Screw connection)
FKM (Seal)
Insertion/withdrawal cycles >= 100
Contact resistance <= 5 m?
Insulation resistance >= 100 M?
Degree of pol...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / NBC-P12MRD/ 0,3-93E/P12FRD with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.