
INDUSTRIAL COMPONENT DATA

NBC-R4AC/10G-R4AC/10G-94F/6,0 1408366 PHOENIX CONTACT Patch cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: NBC-R4AC/10G-R4AC/10G-94F/6,0



Manufacturer	PHOENIX CONTACT
MPN / Reference	NBC-R4AC/10G-R4AC/10G-94F/6,0
Catalog number	1408366
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-C936CA28C4
Generated	2026-11-19

Product Overview

Patch cable
Patch cable, CAT6A, 4 pairs, shielded, non-cross connection (Line), made on both sides with RJ45/IP20 plug-in connectors, outer sheath material: PUR, length: 6.0 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data
Orderkey 1408366
Packing unit 1 pc
GTIN 4046356805070
Weight per Piece (excluding packing) 282.000 g
Custom tariff number 85444210
Country of origin PL (Poland)
Ambient conditions
Degree of protection IP20
General data
Rated current at 40°C 0.5 A
Rated voltage 48 V
Number of positions 8

Alternative short product description Patch cable
Rated voltage (III/3) 72 V (DC)
Cable
Cable type Ethernet 10 Gbit
Cable type (abbreviation) 94F
UL AWM style 20963 (80°C/30 V)
Signal type/category Ethernet CAT6A, 10 Gbps
Cable structure 4x2xAWG26/7; S/FTP
Conductor cross section 4x 2x 0.14 mm²
AWG signal line 26
Conductor structure signal line 7x 0.16 mm
Core diameter including insulation 1.04 mm
Wire colors white/blue-blue, white/orange-orange, white/green-green, white/brown-brown
Twisted pairs 2 cores to the pair
Type of pair shielding Aluminum-lined foil
Overall twist 4 pairs for core
Shielding Tinned copper braided shield
Optical shield covering 70 %
External sheath, color water blue RAL 5021
Outer sheath thickness 0.65 mm
External cable diameter D 6.4 mm ±0.2 mm
Minimum bending radius, fixed installation 4 x D
Minimum bending radius, flexible installation 8 x D
Tensile strength GRP <= 100 N
Cable weight 42 kg/km
Outer sheath, material PUR
Material conductor insulation Foamed PE
Conductor material Bare Cu litz wires
Insulation resistance >= 500 M?*km
Loop resistance <= 290.00 ?/km
Cable capacity 47 nF/km
Wave impedance 100 ? ±5 ? (at 100 MHz)
Near end crosstalk attenuati...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / NBC-R4AC/10G-R4AC/10G-94F/6,0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.