INDUSTRIAL COMPONENT DATA

NBC-R4AC1/0,5-94G/R4AC1-BU 1413159 PHOENIX CONTACT Patch cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: NBC-R4AC1/0,5-94G/R4AC1-BU



Manufacturer	PHOENIX CONTACT
MPN / Reference	NBC-R4AC1/0,5-94G/R4AC1-BU
Catalog number	1413159
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-17646F94CE
Generated	2026-11-19

Product Overview

Patch cable
Patch cable, protection rating: IP20, cable length: 0.5 m, number of poles: 8, 10 GBit/s, CAT6A, Ethernet
Patch cable, degree of protection: IP20, cable length: 0.5 m, number of positions: 8, 10 Gbps, CAT6A, connection method: Pierce connection, Ethernet

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Technical dataProduct propertiesProduct type Data cable preassembled
Sensor type Ethernet
Number of positions 8
Connection profile RJ45
Shielded yes
Data management status
Article revision 04
SignalingStatus display no
Status display present No
Electrical propertiesRated voltage (III/3) 72 V (DC)
Nominal voltage UN 48 V
Nominal current IN 0.5 A

Transmission medium Copper
Transmission speed 10 Gbps
Mechanical propertiesMechanical data
Insertion/withdrawal cycles 200
Insertion force per signal contact 50.00 N
Extraction force per signal contact 30 N
Material specificationsContact material CuSn
Contact surface material Au
Contact carrier material PC
Outer sheath, material PUR
Connection dataConnection technology
Connection method Pierce connection
Conductor connection
Connection method Pierce connection
ConnectorConnection 1
Type Plug straight RJ45
Shielded yes
Insertion/withdrawal cycles >= 750
Degree of protection IP20
Connection 2
Type Plug straight RJ45
Shielded yes
Insertion/withdrawal cycles >= 750
Degree of protection IP20
Cable/lineCable length 0.50 m
Cable type Ethernet 10 Gbit
Cable structure 2x2xAWG26/7, S/FTP
Outer sheath, material PUR
External sheath, color water blue RAL 5021
Conductor structure signal line 6.00 mm +0.2 mm -0.1 mm
AWG signal line 26
Material wire insulation PE
Shielding S/FTP
Test voltage, cable 1000 V DC (1 minute)
Cable insulation resistance 2000 M?*km (500 V)
Coupling resistance 30.00 m?/m (30 MHz)
Halogen-free according to IEC 60754-1
Flame resi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / NBC-R4AC1/0,5-94G/R4AC1-BU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.