INDUSTRIAL COMPONENT DATA

NBC-R4OC/0,2-BC6A/R4OC 1472597 PHOENIX CONTACT Patch cable, RJ45/IP20 straight to RJ45/IP20 straight, cable ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: NBC-R4OC/0,2-BC6A/R4OC



Manufacturer	PHOENIX CONTACT
MPN / Reference	NBC-R4OC/0,2-BC6A/R4OC
Catalog number	1472597
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-192F4BECE6
Generated	2026-11-18

Product Overview

Patch cable, RJ45/IP20 straight to RJ45/IP20 straight, cable length: 0.2m, number of poles: 8, connection cross-section: AWG 26-26, 4x2xAWG26/7; S/FTP, Grey
Patch cable, protection rating: IP20, cable length: 0.2 m, CAT6A, connection type: Pierce connection, connection section: AWG 26- 26, cable output: straight, Ethernet
Patch cable, degree of protection: IP20, cable length: 0.2 m, CAT6A, connection method: Pierce connection, connection cross section: AWG 26- 26, cable outlet: straight, Ethernet

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Technical dataProduct propertiesSensor type Ethernet
Shielded yes
Cable outlet straight
Insulation characteristics
Overvoltage category I
Degree of pollution 2
Electrical propertiesRated voltage (III/2) 72 V
Power transmission PoE++
Material specificationsFlammability rating according to UL 94 V0
Contact material Brass

Contact surface material Au
Contact carrier material PC
Outer sheath, material LSZH
Connection dataConnection technology
Connection method Pierce connection
Conductor connection
Connection method Pierce connection
ConnectorConnection 1
Type Plug straight RJ45
Handle color gray
Insertion/withdrawal cycles >= 750
Degree of protection IP20
Ambient temperature (operation) -20 °C ... 80 °C
Connection 2
Type Plug straight RJ45
Handle color gray
Insertion/withdrawal cycles >= 750
Degree of protection IP20
Ambient temperature (operation) -20 °C ... 80 °C
Cable/lineCable length 0.20 m
Ethernet, Type B, 8-pos., CAT6A, LSZH [BC6A]
Shielded yes
Cable type Ethernet, Type B, 8-pos., CAT6A, LSZH
Cable type (abbreviation) BC6A
Cable structure 4x2xAWG26/7; S/FTP
External cable diameter 6.5 mm ±0.3 mm
Outer sheath, material LSZH
External sheath, color gray
Thickness, outer sheath approx. 0.7 mm
Conductor material Bare Cu litz wires
Conductor structure signal line 7x 0.16 mm
AWG signal line 26
Material wire insulation PE
Single wire, number of litz wires 8
Wire diameter incl. insulation 1 mm
Single wire, cross section [AWG] 26
Shielding S/FTP
Optical shield covering 70 %
Cable ins...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / NBC-R4OC/0,2-BC6A/R4OC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.