INDUSTRIAL COMPONENT DATA

NBC-M12MSD/ 5,0-93E 1407358 PHOENIX CONTACT Network cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: NBC-M12MSD/ 5,0-93E



Manufacturer	PHOENIX CONTACT
MPN / Reference	NBC-M12MSD/ 5,0-93E
Catalog number	1407358
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-3C585F3EF0
Generated	2026-11-19

Product Overview

Network cable
Network cable, CAT5 Ethernet (100 MBit/s), 4-pole, shielded (Advanced Shielding Technology), M12 straight connector, encoding: D/IP67, to free cable end, cable length: 5 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data
Orderkey 1407358
Packing unit 1 pc
Catalog page Page 403 (C-2-2017)
GTIN 4046356774864
Weight per Piece (excluding packing) 236.000 g
Custom tariff number 85444210
Country of origin PL (Poland)
Dimensions
Length of cable 5 m
Ambient conditions
Degree of protection IP65
IP67

Ambient temperature (operation) -25 °C ... 85 °C (M12 connector)
General data
Note Further products with variable cable type and variable cable length can be found in the accessories section
Rated current at 40°C 4 A (Plug/socket in accordance with IEC 61076-2-101, cable technical data is to be observed)
Rated voltage 48 V AC
60 V DC
Number of positions 4
Signal type/category Ethernet CAT5 (IEC 11801), 100 Mbps
Standards/regulations M12 connector IEC 61076-2-101
Contact material CuSn
Contact carrier material TPU GF
Contact surface material Ni/Au
Characteristics head 1
Head type Plug straight M12 SPEEDCON / IP67
No. of positions (pin connector pattern) 4
Coding D (Data)
Color black
Material (component) CuZn (Contact)
Ni/Au (Contact surface)
PA (Contact carriers)
TPU, hardly inflammable, self-extinguishing (Grip)
Zinc die-cast, nickel-plated (Screw connection)
Insulation resistance >= 100 M?
Insertion/withdrawal cycles >= 100
Torque 0.4 Nm
Ambient temperature (operation) -25 °C ... 90 °C
Characteristics head 2
Head type free cable end
Color black
Standards and Regulations
Standard designation M12 connector
Standards/regulations IEC 61076-2-101
Cable
Cable type PUR ETHERNET 2x2 FLEX
Cable t...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / NBC-M12MSD/ 5,0-93E with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.