INDUSTRIAL COMPONENT DATA

NBC-M12FSD/ 1,0-93B/R4QC 1407548 PHOENIX CONTACT Network cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: NBC-M12FSD/ 1,0-93B/R4QC



Manufacturer	PHOENIX CONTACT
MPN / Reference	NBC-M12FSD/ 1,0-93B/R4QC
Catalog number	1407548
Category	Data cable
Minimum order	1 Pcs
Document ID	EO-D311568958
Generated	2026-11-19

Product Overview

Network cable
Network cable, PROFINET CAT5 (100 MBit/s), EtherCAT® CAT5 (100 MBit/s), 4-pole, shielded (Advanced Shielding Technology), Straight female M12, coding: D / IP67, a Straight RJ45 Push-pull connector / IP67, cable length: 1 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data
Orderkey 1407548
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 399 (C-2-2017)
GTIN 4046356778534
Weight per Piece (excluding packing) 119.100 g
Custom tariff number 85444210
Country of origin PL (Poland)
Dimensions
Length of cable 1 m
Ambient conditions
Degree of protection IP65 (M12 connector)

IP67 (M12 connector)
IP67 (RJ45 connector)
Ambient temperature (operation) -25 °C ... 85 °C (M12 connector)
-25 °C ... 60 °C (RJ45 connector)
General data
Note This product corresponds to the PROFINET Cabling and Interconnection Technology Guideline for PROFINET regulations, version 2.00, order no: 2.252, Chapter 8.2 Connectors for Outside Environment (Balanced cabling)
Further products with variable cable type and variable cable length can be found in the accessories section
Rated current at 40°C 1 A
Rated voltage 48 V AC
60 V DC
Number of positions 4
Signal type/category PROFINET CAT5 (IEC 11801), 100 Mbps
EtherCAT®CAT5 (IEC 11801), 100 Mbps
Standards/regulations M12 connector IEC 61076-2-101
Contact material CuSn
Contact carrier material TPU GF
Contact surface material Ni/Au
Housing material Plastic
Characteristics head 1
Head type Plug straight RJ45 Push Pull / IP67
No. of positions (pin connector pattern) 4 (8)
Color black
Material (component) CuSn (Contact)
Ni/Au (Contact surface)
PC (Contact carriers)
PA GF (Housing)
Insertion/withdrawal cycles >= 750
Ambient temperature (operation) -40 °C ... 70 °C
Characteristics head 2
Head type S...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / NBC-M12FSD/ 1,0-93B/R4QC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.