INDUSTRIAL COMPONENT DATA

OTTA 6-P/P YE 0790621 PHOENIX CONTACT Bolt connection terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: OTTA 6-P/P YE



Manufacturer	PHOENIX CONTACT
MPN / Reference	OTTA 6-P/P YE
Catalog number	0790621
Category	Feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-83ECFD5124
Generated	2026-11-19

Product Overview

Bolt connection terminal block
Stud connection terminal, with threaded sockets for test sockets to accommodate test pins, nominal voltage: 800 V, nominal current: 41 A, number of connections: 2, connection type: Stud connection, 1st floor, Dimensioning section: 6 mm², mounting class: NS 35/7.5, NS 35/15, NS 32, color: yellow

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Enclosures connectivity

Additional Product Information

Key Commercial Data
Orderkey 0790621
Packing unit 50 pc
Minimum order quantity 50 pc
Note Made to Order (non-returnable)
GTIN 4046356649834
Weight per Piece (excluding packing) 21.470 g
Custom tariff number 85369010
Country of origin IN (India)
General
Number of levels 1
Number of connections 2

Potentials 1
Nominal cross section 6 mm²
Color yellow
Insulating material PA
Flammability rating according to UL 94 V0
Rated surge voltage 8 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 1.31 W
Maximum load current 41 A (with 6 mm² conductor cross section)
Nominal current IN 41 A
Nominal voltage UN 800 V (the nominal voltage applies to insulated cable lugs)
Open side panel Yes
Shock protection test specification DIN EN 50274 (VDE 0660-514):2002-11
Back of the hand protection guaranteed
Finger protection guaranteed
Note regarding shock protection
Result of surge voltage test Test passed
Surge voltage test setpoint 9.8 kV
Result of power-frequency withstand voltage test Test passed
Power frequency withstand voltage setpoint 2 kV
Result of the test for mechanical stability of terminal points (5 x conductor connection) Test passed
Result of tight fit on support Test passed
Tight fit on carrier NS 32/NS 35
Setpoint 5 N
Result of voltage-drop test Test passed
Requirements, voltage drop <= 3.2 mV
Result of temperature-rise test Test passed
Short circuit stability result Test passed
Conductor cross section short ci...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / OTTA 6-P/P YE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.