

INDUSTRIAL COMPONENT DATA

IB IL 24 DO 32/HD-PAC 2862822 PHOENIX CONTACT Inline terminal

Brand: PHOENIX CONTACT | Manufacturer Part Number: IB IL 24 DO 32/HD-PAC



Manufacturer	PHOENIX CONTACT
MPN / Reference	IB IL 24 DO 32/HD-PAC
Catalog number	2862822
Category	Fieldbus, decentr. periphery - digital I/O module
Minimum order	1 Pcs
Document ID	EO-B2E697107A
Generated	2026-09-21

Product Overview

Inline terminal

Inline, Digital output module, Digital outputs:32, 24 VDC, 500 mA, connection technology:1 driver, transmission speed on the local bus:500 kBit/s, protection index: IP20, including Inline connectors and marking fields

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > I/O**

Additional Product Information

Key Commercial Data

Orderkey 2862822

Packing unit 1 pc

Catalog page Page 153 (C-6-2017)

GTIN 4017918907617

Weight per Piece (excluding packing) 202.910 g

Custom tariff number 85389091

Country of origin DE (Germany)

Note

Utilization restriction 1

Dimensions

Dimensional drawing

Width 48.8 mm

Height 119.8 mm

Depth 71.5 mm

Note on dimensions Housing dimensions

Ambient conditions

Ambient temperature (operation) -25 °C ... 55 °C

Ambient temperature (storage/transport) -25 °C ... 85 °C

Permissible humidity (operation) 10 % ... 95 % (non-condensing)

Permissible humidity (storage/transport) 10 % ... 95 % (non-condensing)

Air pressure (operation) 70 kPa ... 106 kPa (up to 3000 m above sea level)

80 kPa ... 106 kPa (up to 3000 m above sea level, in ATEX Zone 2)

Air pressure (storage/transport) 70 kPa ... 106 kPa (up to 3000 m above sea level)

Degree of protection IP20

General

Mounting type DIN rail

Net weight 202.91 g

Note on weight specifications with connectors

Operating mode Process data operation with 2 words

Diagnostics messages Short-circuit / overload of the digital outputs Error message in the diagnostic code (bus) and display (2 Hz) via the LED (D) on the module

Interfaces

Designation Inline local bus

No. of channels 2

Connection method Inline data jumper

Transmission speed 500 kbps

Inline potentials

Designation Communications power (UL)

Supply voltage 7.5 V DC (via voltage jumper)

Current consumption max. 140 mA

Power consumption max. 1.05 W

Designation Segment circuit supply...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / IB IL 24 DO 32/HD-PAC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.