INDUSTRIAL COMPONENT DATA

# SSL 2,5 3043815 PHOENIX CONTACT Panel feed-through

**Brand: PHOENIX CONTACT | Manufacturer Part Number: SSL 2,5**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | SSL 2,5 |
| Catalog number | 3043815 |
| Category | Installation clamp for meters |
| Minimum order | 50 Pcs |
| Document ID | EO-AFE17C6714 |
| Generated | 2026-11-18 |

## Product Overview

Panel feed-through
Feedthrough, width: 5.2 mm, colour: grey
Panel feed-through, width: 5.2 mm, color: gray

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > Modular TBs |

## Additional Product Information

Technical dataProduct propertiesProduct type Mounting material
Data management status
Article revision 02
Insulation characteristics
Overvoltage category III
Electrical propertiesRated surge voltage 8.00 kV
DimensionsDimensional drawing
Width 5.2 mm
Plate thickness 0.8 mm ... 3 mm
Installation dimensions
Length of the assembly cutout 16.6 mm
Material specificationsColor gray (RAL 7042)
Material PA
Flammability rating according to UL 94 V0

Insulating material group I
Insulating material PA
Static insulating material application in cold -60 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 130 °C
Relative insulation material temperature index (Elec., UL 746 B) 130 °C
Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R26 HL 1 - HL 3
Calorimetric heat release NFPA 130 (ASTM E 1354) 28 MJ/kg
Surface flammability NFPA 130 (ASTM E 162) passed
Specific optical density of smoke NFPA 130 (ASTM E 662) passed
Smoke gas toxicity NFPA 130 (SMP 800C) passed
Environmental and real-life conditionsAmbient conditions
Ambient temperature (operation) -60 °C ... 105 °C (max. short-term operating temperature RTI Elec.)
Ambient temperature (storage/transport) -25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly) -5 °C ... 70....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SSL 2,5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.