
INDUSTRIAL COMPONENT DATA

# UW 25/S 3073377 PHOENIX CONTACT Panel feed-through terminal block

**Brand: PHOENIX CONTACT | Manufacturer Part Number: UW 25/S**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | UW 25/S |
| Catalog number | 3073377 |
| Category | Panel feed-through terminal block |
| Minimum order | 25 Pcs |
| Document ID | EO-99FAE73ACE |
| Generated | 2026-11-18 |

## Product Overview

Panel feed-through terminal block
Borne grommets, connection type: Screw connection with traction capsule, Screw connection with traction capsule, number of poles: 1, charging current: 101 A, section: 6 mm² - 35 mm², conductor connection direction with respect to the plug direction: 0 °, width: 15.1 mm, color: grey
Design terminal, connection type: Screw connection with cage, Screw connection with cage, number of poles: 1, load current: 101 A, cross-section: 6 mm2 - 35 mm2, conductor connection direction to insertion direction: 0 °, width: 15.1 mm, colour: grey

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > PCB Connectors (PCC) |

## Additional Product Information

Key Commercial Data
Orderkey 3073377
Packing unit 25 pc
Catalog page Page 614 (C-1-2013)
GTIN 4046356344623
Weight per Piece (excluding packing) 54.550 g
Custom tariff number 85369010
Country of origin CN (China)
General

Number of levels 1
Number of connections 2
Nominal cross section 25 mm²
Color gray
Insulating material PA
Flammability rating according to UL 94 V0
Maximum load current 125 A
Rated surge voltage 6 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Connection in acc. with standard IEC 60947-7-1
Nominal current IN 101 A
Maximum load current 125 A
Nominal voltage UN 800 V (with spacer plate)
Open side panel No
Number of positions 1
Dimensions
Width 15.1 mm
Pitch 15.1 mm
Plate thickness 1 mm ... 6 mm
Connection data
Note Terminal sleeve
Connection side outside
Connection method Screw connection
Note Note: Product releases, connection cross sections and notes on connecting aluminum cables can be found in the download area.
Conductor cross section solid min. 6 mm²
Conductor cross section solid max. 35 mm²
Conductor cross section flexible min. 10 mm²
Conductor cross section flexible max. 25 mm²
Conductor cross section AWG min. 10
Conductor cross section AWG max. 2
Conductor cross section flexible, with ferrule without plastic sleeve min. 4 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 25 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 4 mm²
Conductor cross section flexible, with...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UW 25/S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.