INDUSTRIAL COMPONENT DATA

# VS-PPC-F1-SCRJ-MNNA-1C-F 1405235 PHOENIX CONTACT Panel mounting frames

**Brand: PHOENIX CONTACT | Manufacturer Part Number: VS-PPC-F1-SCRJ-MNNA-1C-F**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | VS-PPC-F1-SCRJ-MNNA-1C-F |
| Catalog number | 1405235 |
| Category | Fixing element for industrial connectors |
| Minimum order | 1 Pcs |
| Document ID | EO-EB17D7F922 |
| Generated | 2026-11-19 |

## Product Overview

Panel mounting frames
Recessed Push-Pull frame, IP67, metallic, with Freenet system, for round mounting section, with gasket and SC-RJ coupling (for POF, PCF & GOF)

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > Field Device Connectors (FDC) |

## Additional Product Information

Key Commercial Data
Orderkey 1405235
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 373 (C-2-2017)
GTIN 4046356334785
Weight per Piece (excluding packing) 60.000 g
Custom tariff number 85389099
Country of origin DE (Germany)
Mechanical characteristics
Number of positions 2
Number of slots 1
Locking type Push Pull

Insertion/withdrawal cycles = 100
Color silver
Degree of protection IP65/IP67
Type SCRJ, IP65/67, version 14
Note This product corresponds to the PROFINET Cabling and Interconnection Technology Guideline for PROFINET regulations, version 2.00, order no: 2.252, Chapter 8.2 Connectors for Outside Environment (Balanced cabling) and chapter 13 Application specific Cabling and Interconnection Technology (AIDA)
Ambient conditions
Ambient temperature (operation) -40 °C ... 70 °C
Degree of protection IP67 (IP65/67)
Material data
Flammability rating according to UL 94 V0
Housing material Zinc die-cast
Housing surface material Nickel-plated
Material Metal
Electrical characteristics
Number of positions 2
Degree of pollution 2
Standards and Regulations
Flammability rating according to UL 94 V0
Environmental Product Compliance
REACh SVHC Lead 7439-92-1
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab “Downloads”, Category “Manufacturer's declaration”
Classifications
eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027261200eCl@ss 7.027440210eCl@ss 8.027440210eCl@ss 9.0274...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VS-PPC-F1-SCRJ-MNNA-1C-F with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**
Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.