INDUSTRIAL COMPONENT DATA

VS-PPC-F1-SCRJ-MNNA-1RF 1405374 PHOENIX CONTACT Panel mounting frames

Brand: PHOENIX CONTACT | Manufacturer Part Number: VS-PPC-F1-SCRJ-MNNA-1RF



Manufacturer	PHOENIX CONTACT
MPN / Reference	VS-PPC-F1-SCRJ-MNNA-1RF
Catalog number	1405374
Category	Fixing element for industrial connectors
Minimum order	1 Pcs
Document ID	EO-2079DAB03D
Generated	2026-11-18

Product Overview

Panel mounting frames
Recessed frame SC-RJ, IP67, for Push-Pull locking, metallic, with Freenet system, for rectangular mounting section, with gasket and SC-RJ coupling (for POF, PCF & GOF), without fixing screws
SC-RJ panel mounting frame, IP67, for push-pull interlocking, metal, with Freenet system, for rectangular mounting cutout, with seal and SC-RJ coupling (for POF, PCF, and GOF), without mounting screws

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Technical dataProduct propertiesProduct type Panel-mount frame
Application Freenet
Type SC-RJ
Number of positions 2
Connection profile SC-RJ
Type SC-RJ
Cable outlet straight
Data management status
Article revision 04
Insulation characteristics
Degree of pollution 2

Electrical propertiesTransmission medium FO
Connection dataConnection technology
Connection method Push-Pull
DimensionsDimensional drawing
Width 22.2 mm
Height 42 mm
Mechanical characteristics
Ferrule diameter 2.50 mm
Material specificationsColor silver
Material Metal
Flammability rating according to UL 94 V0
Housing material Metal
Housing surface material nickel-plated
Cable/lineResistance to oil yes
Flame resistance yes
FO cable
Number of fibers 2
Fiber POF, PCF, GOF
Fiber type GOF, PCF, POF
Transmission medium FO
Mechanical propertiesMechanical data
Insertion/withdrawal cycles >= 500
Environmental and real-life conditionsAmbient conditions
Degree of protection IP67 (IP65/67)
IP65/IP67
Ambient temperature (operation) -40 °C ... 70 °C
Ambient temperature (storage/transport) -40 °C ... 70 °C
Ambient temperature (assembly) 0 °C ... 50 °C
Resistance to oil yes
Standards and regulationsFlame resistance yes
Resistance to oil yes
MountingMounting type Wall mounting

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VS-PPC-F1-SCRJ-MNNA-1RF with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.