INDUSTRIAL COMPONENT DATA

VS-PPC-F2-MSTB-MNNA-1C-SPSA5 1405248 PHOENIX CONTACT Panel mounting frames

Brand: PHOENIX CONTACT | Manufacturer Part Number: VS-PPC-F2-MSTB-MNNA-1C-SPSA5



Manufacturer	PHOENIX CONTACT
MPN / Reference	VS-PPC-F2-MSTB-MNNA-1C-SPSA5
Catalog number	1405248
Category	Fixing element for industrial connectors
Minimum order	1 Pcs
Document ID	EO-CFE3B8BDAF
Generated	2026-11-18

Product Overview

Panel mounting frames
Recessed frame MSTB, IP67, for push-pull locking, metal, with integrated contact insert for conductor connection, spring connection, 24 V, for round mounting opening, with gasket, without fixing screws

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data
Orderkey 1405248
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 368 (C-2-2017)
GTIN 4046356334808
Weight per Piece (excluding packing) 118.200 g
Custom tariff number 85366990
Country of origin DE (Germany)
Mechanical characteristics
Number of positions 5
Locking type Push Pull
Connection method Spring-cage connection

Conductor cross section 0.75 mm² ... 2.5 mm²
Connection cross section AWG 18 ... 13
Color silver
Degree of protection IP65/IP67
Type Power, IP65/67, version 14
Ambient conditions
Ambient temperature (operation) -40 °C ... 70 °C
Material data
Flammability rating according to UL 94 V0
Housing material Zinc die-cast
Housing surface material Nickel-plated
Contact carrier material PA
Contact material Copper alloy
Contact surface material Gold over nickel
Material Metal
Sealing material NBR
Seal material NBR
Electrical characteristics
Number of positions 5
Degree of pollution 2
Rated voltage (III/3) 24 V
Standards and Regulations
Flammability rating according to UL 94 V0
Environmental Product Compliance
REACh SVHC Lead 7439-92-1
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab “Downloads”, Category “Manufacturer's declaration”
Classifications
eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027261200eCl@ss 7.027440210eCl@ss 8.027440210eCl@ss 9.027440210
ETIM 3.0EC002310ETIM 4.0EC002310ETIM 5.0EC002310ETIM 6.0EC002310
UNSPSC 6.0131261501UNSPS...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VS-PPC-F2-MSTB-MNNA-1C-SPSA5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES
Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.