INDUSTRIAL COMPONENT DATA

# ME 22,5 F-UTG BUS/10+2 GN 2706043 PHOENIX CONTACT Mounting base housing

**Brand: PHOENIX CONTACT | Manufacturer Part Number: ME 22,5 F-UTG BUS/10+2 GN**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | ME 22,5 F-UTG BUS/10+2 GN |
| Catalog number | 2706043 |
| Category | Extruded profile modular housing |
| Minimum order | 10 Pcs |
| Document ID | EO-047711C736 |
| Generated | 2026-11-19 |

## Product Overview

Mounting base housing
Rail box, Bottom of the housing with metal pin, flat design, without ventilation slits, width: 22.6 mm, height: 99 mm, depth: 84.8 mm, color: green (6021), cross bridge: integrated bus connector, number of poles cross connector: 10+2, Bus connector: 10 contacts in parallel, 2 contacts in series
DIN rail housing, Lower housing part with metal foot catch, flat design, without vents, width: 22.6 mm, height: 99 mm, depth: 84.8 mm, color: green (similar RAL 6021), cross connection: integrated bus connector, number of positions cross connector: 10+2, Bus connector: 10 parallel contacts, 2 serial contacts

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > Housing (HS) |

## Additional Product Information

Technical dataNotesAssembly note Refer to the data sheet for the range in the download area.
Recommendation Material of contact pads for bus connector, galvanic gold (hard gold)
Product propertiesProduct type Enclosure bottom part
Housing type DIN rail housing
Housing series ME
Product family ME 22,5..
Type Lower housing parts without vents, housing cover necessary to complete the module
Max. number of positions 0)
Type Lower housing part with metal foot catch, flat design

Ventilation openings present no
Data management status
Article revision 15
DimensionsDimensional drawing
Width 22.6 mm
Height 99 mm
Depth 84.8 mm
Depth from top edge of DIN rail 78.2 mm
Depth from top edge of DIN rail to support point on upper part 46 mm
PCB design
PCB thickness 1.4 mm ... 1.8 mm
Material specificationsColor (Housing) green (RAL 6021)
Flammability rating according to UL 94 V0
CTI according to IEC 60112 600
Housing material Polyamide
Surface characteristics untreated
Environmental and real-life conditionsPower dissipation single housing for 20 °C
Ambient temperature 20 °C
Reduction factor 1
Mounting position vertical
Power dissipation 5.5 W
Power dissipation single housing for 30 °C
Ambient temperature 30 °C
Reduction factor 0.91
Mounting position vertical
Power dissipation 5 W
Power dissipation single housing for 40 °C
Ambient temperature 40 °C
Reduction factor 0.81
Mounting position vertical
Power dissipation 4.4 W
Power dissipation single housing for 50 °C
Ambient temperature 50 °C
Reduc...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ME 22,5 F-UTG BUS/10+2 GN with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.