INDUSTRIAL COMPONENT DATA

VS-PNRJ45-PNRJ45R-93K-1,0 1402514 PHOENIX CONTACT Patch cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: VS-PNRJ45-PNRJ45R-93K-1,0



Manufacturer	PHOENIX CONTACT
MPN / Reference	VS-PNRJ45-PNRJ45R-93K-1,0
Catalog number	1402514
Category	Patch cord copper (twisted pair)
Minimum order	1 Pcs
Document ID	EO-AE859D5AB6
Generated	2026-11-18

Product Overview

Patch cable
Sercos III Patch Cable, Shielded, Star Quad, Flexible AWG 22 (7 wires), RAL 3020 (Traffic Red), RJ45/IP20 Plug, Straight, to RJ45/IP20 Male, Angled, Length: 1.0 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data
Orderkey 1402514
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 321 (PC-2011)
GTIN 4046356622530
Weight per Piece (excluding packing) 22.220 g
Custom tariff number 85444210
Country of origin PL (Poland)
Ambient conditions
Degree of protection IP20
General data
Number of positions 4

Degree of pollution 1
Rated voltage (III/3) 72 V (DC)
Characteristics head 1
Color black
Material (component) CuSn (Contact)
Ni/Au (Contact surface)
PA (Contact carriers)
PA (Housing)
Insertion/withdrawal cycles >= 750
Ambient temperature (operation) -25 °C ... 80 °C
Characteristics head 2
Color black
Material (component) CuSn (Contact)
Ni/Au (Contact surface)
PA (Contact carriers)
PA (Housing)
Insertion/withdrawal cycles >= 750
Ambient temperature (operation) -25 °C ... 80 °C
Standards and Regulations
Flammability rating according to UL 94 V0
Cable
Cable type Sercos III
Cable type (abbreviation) 93K
UL AWM style 21694 (60°C / 600 V)
Signal type/category Sercos CAT5 (IEC 11801), 100 Mbps
Cable structure 1x4xAWG22/7; SF/TQ
Conductor cross section 4x 0.34 mm²
AWG signal line 22
Conductor structure signal line 7x 0.25 mm
Core diameter including insulation approx. 1.55 mm
Wire colors White, yellow, blue, orange
Type of pair shielding Aluminum-lined polyester foil
Overall twist Star quad
Shielding Tinned copper braided shield
External sheath, color signal red RAL 3020
Outer sheath thickness approx. 0.9 mm
External cable diameter D 6.5 mm ±0.2 mm
Minimum bendin...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VS-PNRJ45-PNRJ45R-93K-1,0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.