INDUSTRIAL COMPONENT DATA

# PC 16/ 4-ST-10,16 BUGY CP1,2NZ 1726127 PHOENIX CONTACT Printed-circuit board connector

**Brand: PHOENIX CONTACT | Manufacturer Part Number: PC 16/ 4-ST-10,16 BUGY CP1,2NZ**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | PC 16/ 4-ST-10,16 BUGY CP1,2NZ |
| Catalog number | 1726127 |
| Category | Cable connector |
| Minimum order | 25 Pcs |
| Document ID | EO-4D04E02DE3 |
| Generated | 2026-11-19 |

## Product Overview

Printed-circuit board connector
Connector for printed circuit board, nominal section: 16 mm², color: bluish gray, nominal current: 76 A, nominal voltage (III/2): 1000 V, contact surface: silver, contact type: Female, number of potentials: 4, number of rows: 1, number of poles: 4, number of connections: 4, family of articles: PC 16/.. -ST, pitch: 10.16 mm, connection type: Screw connection with traction capsule, screw clamping form: L Longitudinal slot, conductor connection direction/printed circuit board: 0 °, clamping hook: - without clamping hook, plug-in system: COMBICON PC 16, locking: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > PCB Connectors (PCC) |

## Additional Product Information

Key Commercial Data
Orderkey 1726127
Packing unit 50 pc
Minimum order quantity 50 pc
Note Made to Order (non-returnable)
GTIN 4046356130295
Weight per Piece (excluding packing) 38.110 g
Custom tariff number 85366990
Country of origin PL (Poland)
Dimensions

Length [ l ] 41.5 mm
Width [ w ] 40.48 mm
Height [ h ] 27.8 mm
Pitch 10.16 mm
Dimension a 30.48 mm
General
Range of articles PC 16/..-ST
Number of positions 4
Connection method Screw connection with tension sleeve
Rated voltage (III/3) 1000 V
Connection in acc. with standard EN-VDE
Nominal current IN 76 A
Nominal cross section 16 mm²
Connection data
Conductor cross section solid min. 0.75 mm²
Conductor cross section solid max. 16 mm²
Conductor cross section flexible min. 0.75 mm²
Conductor cross section flexible max. 16 mm²
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.5 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 16 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.5 mm²
Conductor cross section flexible, with ferrule with plastic sleeve max. 10 mm²
Conductor cross section AWG min. 18
Conductor cross section AWG max. 6
2 conductors with same cross section, solid min. 0.75 mm²
2 conductors with same cross section, solid max. 6 mm²
2 conductors with same cross section, stranded min. 0.75 mm²
2 conductors with same cross section, stranded max. 6 mm²
2 conductors with same cross section, stranded, ferrules without plastic sleeve, min....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PC 16/ 4-ST-10,16 BUGY CP1,2NZ with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.