INDUSTRIAL COMPONENT DATA

PC 4/13-GU-6,35 P26 THR 1299283 PHOENIX CONTACT Printed circuit board base case, nominal section: 4 mm², col..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PC 4/13-GU-6,35 P26 THR

PRODUCT IMAGE\nNOT AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	PC 4/13-GU-6,35 P26 THR
Catalog number	1299283
Category	Printed circuit board connector
Minimum order	1 Pcs
Document ID	EO-62627FF687
Generated	2026-11-19

Product Overview

PC 4/13-GU-6,35 P26 THR 1299283 PHOENIX CONTACT Printed circuit board base case, nominal section: 4 mm², col..

STRUCTURED PRODUCT DATA

Technical Specifications

TECHNICAL ATTRIBUTE	VALUE
Connector model (EF007495)	**Fixed connector**
Contact type (EF001587)	**Pin**
Number of plug-in contact rows (EF006935)	**1**
Modular spacing contacts (EF007326)	**6.35 mm**
Modular spacing connections (EF006827)	**6.35 mm**
Rated current In (EF008250)	**24 A**
Rated voltage (EF000228)	**800 V**
Rated surge voltage (EF002993)	**6 kV**
Over voltage category (EF006785)	**III**
Pollution degree (EF006786)	**2**
Material of contact surface (EF004020)	**Tin**
Type of electric connection (EF003961)	**Other**
Diameter connection pin (EF006823)	**1.7 mm**
Length pin (EF006825)	**2.6 mm**
Material insulation body (EF007543)	**Other**

CONTINUED

Technical Specifications

TECHNICAL ATTRIBUTE	VALUE
Housing colour (EF000136)	**Black**
Inflammability class of insulation material according to UL94 (EF002521)	**V0**
Operating temperature (EF002393)	**-40 °C**
Type of fastening (EF002442)	**Other**
Type of banding (EF007011)	**Carton (for SMD)**

Classification & Catalog Path

Catalog path	**PHOENIX CONTACT > PCB Connectors (PCC)**

Additional Product Information

Printed circuit board base case, nominal section: 4 mm², color: black, nominal current: 24 A, nominal voltage (III/2): 800 V, contact surface: Sn, contact connection type: Male, number of rows: 1, number of poles: 13, article family: PC 4/.. -GU-THR, pitch: 6.35 mm, mounting: THR welding/wave soldering, pin arrangement: Zigzag pins M, pin length [P]: 2.6 mm, number of solder pins per potential: 1, plug-in system: COMBICON PC 4, Plug-in face orientation: inverted, locking: without, fixing type: without, packaging type: boxed

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PC 4/13-GU-6,35 P26 THR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.