INDUSTRIAL COMPONENT DATA

PC 4/ 5-ST-7,62BDNZ:ERDE-0V 1966415 PHOENIX CONTACT Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: PC 4/ 5-ST-7,62BDNZ:ERDE-0V



Manufacturer	PHOENIX CONTACT
MPN / Reference	PC 4/ 5-ST-7,62BDNZ:ERDE-0V
Catalog number	1966415
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-9DE2BF072D
Generated	2026-11-19

Product Overview

Printed-circuit board connector
Connector for printed circuit board, nominal section: 4 mm², color: green, nominal current: 20 A, nominal voltage (III/2): 630 V, contact surface: Tin, contact type: Female, number of potentials: 5, number of rows: 1, number of poles: 5, number of connections: 5, family of items: PC 4/.. -ST, pitch: 7.62 mm, connection type: Screw connection with traction capsule, screw clamping form: L Longitudinal slot, conductor connection direction/printed circuit board: 0 °, clamping hook: - Clamping hook, plug-in system: COMBICON PC 4, locking: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data
Orderkey 1966415
Packing unit 50 pc
Minimum order quantity 50 pc
Note Made to Order (non-returnable)
GTIN 4017918913380
Weight per Piece (excluding packing) 20.480 g
Custom tariff number 85366990
Country of origin DE (Germany)
Dimensions

Length [l] 30.7 mm
Width [w] 38.08 mm
Height [h] 18.1 mm
Pitch 7.62 mm
Dimension a 30.48 mm
General
Range of articles PC 4/..-ST
Number of positions 5
Connection method Screw connection with tension sleeve
Rated voltage (III/3) 400 V
Connection in acc. with standard EN-VDE
Nominal current IN 20 A
Nominal cross section 4 mm²
Connection data
Conductor cross section solid min. 0.2 mm²
Conductor cross section solid max. 4 mm²
Conductor cross section flexible min. 0.2 mm²
Conductor cross section flexible max. 4 mm²
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 4 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule with plastic sleeve max. 4 mm²
Conductor cross section AWG min. 24
Conductor cross section AWG max. 10
2 conductors with same cross section, solid min. 0.2 mm²
2 conductors with same cross section, solid max. 2.5 mm²
2 conductors with same cross section, stranded min. 0.2 mm²
2 conductors with same cross section, stranded max. 1.5 mm²
2 conductors with same cross section, stranded, ferrules without plastic sleeve, min. 0.2...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PC 4/ 5-ST-7,62BDNZ:ERDE-0V with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.