INDUSTRIAL COMPONENT DATA

PC 4/ 9-STF-7,62 PA1,3,5,7,9 1009967 PHOENIX CONTACT Printed-circuit board connector PC 4/ 9-STF-7,62 PA1,3,..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PC 4/ 9-STF-7,62 PA1,3,5,7,9



Manufacturer	PHOENIX CONTACT
MPN / Reference	PC 4/ 9-STF-7,62 PA1,3,5,7,9
Catalog number	1009967
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-AD7993C289
Generated	2026-11-18

Product Overview

Printed-circuit board connector - PC 4/ 9-STF-7,62 PA1,3,5,7,9 - 1009967
Connector for printed circuit board, nominal section: 4 mm², color: green, rated current: 20 A, dimensioning voltage (III/2): 630 V, surface contacts: Tin, contact type: Connecting female, Number of potentials: 9, Number of rows: 1, Number of poles per row: 9, number of connections: 9, item family: PC 4/.. -STF, pitch: 7.62 mm, connection type: Screw connection with traction capsule, connection direction conductor/printed circuit board: 0 °, Stecksystem: POWER COMBICON 4, Lock: Locking by screw, type of packaging: boxed packaging
PCB connector, nominal cross section: 4 mm2, color: green, nominal current: 20 A, rated voltage (III/2): 630 V, contact surface: Tin, contact connection type: Socket, number of potentials: 5, number of rows: 1, number of positions: 9, number of connections: 5, product range: PC 4/..-STF, pitch: 7.62 mm, connection method: Screw connection with tension sleeve, screw head form: L Slotted, conductor/PCB connection direction: 0 °, locking clip: - Locking clip, plug-in system: COMBICON PC 4, locking: Screw locking mechanism, mounting: Screw flange, type of packaging: packed in cardboard

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Technical dataProduct propertiesProduct line COMBICON Connectors L
Product type PCB connector
Product family PC 4/..-STF
Number of positions 9
Pitch 7.62 mm

Number of connections 5
Number of rows 1
Number of potentials 5
Electrical propertiesNominal current IN 20 A
Nominal voltage UN 630 V
Degree of pollution 3
Contact resistance 0.5 m?
Rated voltage (III/3) 400 V
Rated surge voltage (III/3) 6 kV
Rated voltage (III/2) 630 V
Rated surge voltage (III/2) 6 kV
Rated voltage (II/2) 1000 V
Rated surge voltage (II/2) 6 kV
Connection dataConnection technology
Type Standard
Connector system COMBICON PC 4
Nominal cross section 4 mm²
Contact connection type Socket
Interlock
Locking type Screw locking mechanism
Mounting flange Screw flange
Tightening torque 0.3 Nm ... 0.7 Nm
Conductor connection
Connection method Screw connection with tension sleeve
Conductor/PCB connection direction 0 °
Conductor cross section rigid 0.2 mm² ... 4 mm²
Conductor cross section flexible 0.2 mm² ... 4 mm²
Conductor cross section AWG 24 ... 10
Conductor cross section flexible, with ferrule without plastic sleeve 0.25 mm² ... 4 mm²
Conductor cross section, flexible, with ferrule, with plastic sleeve 0.25 mm² ... 4 mm²
2 conductors with same cross section, solid 0.2 mm² ... 2.5 mm²
2 conductors with same cross section, flexible 0.2 mm² ... 1.5 mm²
2 conductors with same cross section, flexible, with ferrule without plastic sleeve 0.25 mm² ... 1.5 mm²
2 conductors with the same cross section, flexible, with TWI...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PC 4/ 9-STF-7,62 PA1,3,5,7,9 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.