INDUSTRIAL COMPONENT DATA

# PC 6-16/ 3-G1F-10,16 BK 1710322 PHOENIX CONTACT Feed-through header

**Brand: PHOENIX CONTACT | Manufacturer Part Number: PC 6-16/ 3-G1F-10,16 BK**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | PC 6-16/ 3-G1F-10,16 BK |
| Catalog number | 1710322 |
| Category | Printed circuit board connector |
| Minimum order | 1 Pcs |
| Document ID | EO-80EB8C5611 |
| Generated | 2026-11-19 |

## Product Overview

PC 6-16/ 3-G1F-10,16 BK 1710322 PHOENIX CONTACT Feed-through header

STRUCTURED PRODUCT DATA

## Technical Specifications

| TECHNICAL ATTRIBUTE | VALUE |
|---|---|
| Connector model (EF007495) | **Fixed connector** |
| Contact type (EF001587) | **Pin** |
| Number of poles (EF001391) | **3** |
| Number of plug-in contact rows (EF006935) | **1** |
| Modular spacing contacts (EF007326) | **10.16 mm** |
| Modular spacing connections (EF006827) | **10.16 mm** |
| Rated current In (EF008250) | **76 A** |
| Rated voltage (EF000228) | **1000 V** |
| Rated surge voltage (EF002993) | **8 kV** |
| Over voltage category (EF006785) | **III** |
| Pollution degree (EF006786) | **2** |
| Material of contact surface (EF004020) | **Silver** |
| Type of electric connection (EF003961) | **Other** |
| Diameter connection pin (EF006823) | **1.7 mm** |
| Length pin (EF006825) | **4 mm** |

CONTINUED

## Technical Specifications

| TECHNICAL ATTRIBUTE | VALUE |
|---|---|
| **Material insulation body (EF007543)** | **Other** |
| Housing colour (EF000136) | **Black** |
| Inflammability class of insulation material according to UL94 (EF002521) | **V0** |
| Operating temperature (EF002393) | **-40 °C** |
| Type of fastening (EF002442) | **Other** |
| Type of banding (EF007011) | **Carton (for SMD)** |

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | **PHOENIX CONTACT > PCB Connectors (PCC)** |

## Additional Product Information

Feed-through header
Printed circuit board base housing, nominal section: 16 mm², color: black, nominal current: 76 A (41 A in combination with PC 6 connector), nominal voltage (III/2): 1000 V, contact surface: silver, contact type: Male, number of potentials: 3, number of rows: 1, number of poles: 3, number of connections: 3, family of articles: PC 6-16/.. -G1F, pitch: 10.16 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 4 mm, number of solder pins per potential: 3, plug-in system: COMBICON PC 16, Plug-in face orientation: Standard, locking: Screw lock, fixing type: Air clamping (thread), packaging type: boxed

### REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PC 6-16/ 3-G1F-10,16 BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**
Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.