
INDUSTRIAL COMPONENT DATA

PC 6-16/ 5-GF-10,16 1913743 PHOENIX CONTACT Feed-through header

Brand: PHOENIX CONTACT | Manufacturer Part Number: PC 6-16/ 5-GF-10,16



Manufacturer	PHOENIX CONTACT
MPN / Reference	PC 6-16/ 5-GF-10,16
Catalog number	1913743
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-13CD206E33
Generated	2026-11-19

Product Overview

Feed-through header
Base housing printed circuit board, nominal section: 6 mm², color: green, rated current: 76 A (41 A in combination with PC 6 connector), sizing voltage (III/2): 1000 V, surface contacts: silver, contact type: Male, Number of potentials: 5, Number of rows: 1, Number of poles per row: 5, number of connections: 5, Item family: PC 6-16/.. -GF, pitch: 10.16 mm, mounting: Wave welding, pin arrangement: Linear pin arrangement, pin length [P]: 4 mm, Stecksystem: POWER COMBICON 16, Locking: Screw locking, packing type: boxed packaging, 76 A rated current is valid in combination with PC 16 family connectors. In combination with PC 6 connectors, 41 A (50A according to UL) is reached.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data
Orderkey 1913743
Packing unit 50 pc
Minimum order quantity 50 pc
Catalog page Page 195 (CC-2002)
GTIN 4017918179229
Weight per Piece (excluding packing) 22.090 g
Custom tariff number 85366930
Country of origin PL (Poland)

Dimensions
Length [l] 32 mm
Width 68.56 mm
Pitch 10.16 mm
Dimension a 40.64 mm
Width [w] 68.56 mm
Height [h] 17.71 mm
Height 13.71 mm
Length of the solder pin 4 mm
Length 32 mm
General
Range of articles PC 6-16/..-GF
Rated surge voltage (III/3) 6 kV
Rated surge voltage (III/2) 8 kV
Rated surge voltage (II/2) 8 kV
Rated voltage (III/2) 1000 V
Rated voltage (II/2) 1000 V
Nominal current IN 41 A
Color green
Number of positions 5
Standards and Regulations
Connection in acc. with standard CUL
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Classifications
eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss 7.027440402eCl@ss 8.027440402eCl@ss 9.027440402
ETIM 3.0EC001121ETIM 4.0EC002637ETIM 5.0EC002637ETIM 6.0EC002637
UNSPSC 6.0130211810UNSPSC 7.090139121409UNSPSC 1139121409UNSPSC 12.0139121409UNSPSC 13.239121409

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PC 6-16/ 5-GF-10,16 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES
Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.