
INDUSTRIAL COMPONENT DATA

PC 6-16/ 5-GF-10,16 GY(135)CP2,4 1971523 PHOENIX CONTACT Feed-through header

Brand: PHOENIX CONTACT | Manufacturer Part Number: PC 6-16/ 5-GF-10,16 GY(135)CP2,4



Manufacturer	PHOENIX CONTACT
MPN / Reference	PC 6-16/ 5-GF-10,16 GY(135)CP2,4
Catalog number	1971523
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-D2B67B9D1D
Generated	2026-11-19

Product Overview

Feed-through header
Printed circuit board base housing, nominal section: 6 mm², color: gray, nominal current: 76 A (41 A in combination with PC 6 connector), nominal voltage (III/2): 1000 V, contact surface: silver, contact type: Male, number of potentials: 3, number of rows: 1, number of poles: 5, number of connections: 3, article family: PC 6-16/.. -GF, pitch: 10.16 mm, mounting: Wave welding, pin arrangement: Linear pin arrangement, pin length [P]: 4 mm, number of solder pins per potential: 3, plug-in system: COMBICON PC 16, Plug-in face orientation: Standard, locking: Screw lock, fixing type: Air clamping (thread), packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data
Orderkey 1971523
Packing unit 50 pc
Minimum order quantity 50 pc
Note Made to Order (non-returnable)
GTIN 4017918931018
Weight per Piece (excluding packing) 18.730 g
Custom tariff number 85366990
Country of origin PL (Poland)

Dimensions
Length [l] 32 mm
Width 68.56 mm
Pitch 10.16 mm
Dimension a 40.64 mm
Width [w] 68.56 mm
Height [h] 17.71 mm
Height 13.71 mm
Length of the solder pin 4 mm
Length 32 mm
General
Range of articles PC 6-16/..-GF
Nominal current IN 41 A
Color gray
Number of positions 5
Standards and Regulations
Connection in acc. with standard CUL
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Classifications
eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss 7.027440402eCl@ss 8.027440402eCl@ss 9.027440402
ETIM 3.0EC001121ETIM 4.0EC002637ETIM 5.0EC002637ETIM 6.0EC002637
UNSPSC 6.0130211810UNSPSC 7.090139121409UNSPSC 1139121409UNSPSC 12.0139121409UNSPSC 13.239121409

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PC 6-16/ 5-GF-10,16 GY(135)CP2,4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES
Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.