INDUSTRIAL COMPONENT DATA

PC 6/ 4-GL3-7,62 1717035 PHOENIX CONTACT Housing base printed circuit board, nominal current: 41 A, number o..

Brand: PHOENIX CONTACT | Manufacturer Part Number: PC 6/ 4-GL3-7,62

PRODUCT IMAGE\nNOT AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	PC 6/ 4-GL3-7,62
Catalog number	1717035
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-F8BE891CB5
Generated	2026-11-18

Product Overview

Housing base printed circuit board, nominal current: 41 A, number of poles: 4, pitch: 7.62 mm, color: black, surface of contact: Tin, assembly: wave Soldering
Printed circuit board base housing, nominal section: 6 mm², color: green, nominal current: 41 A, nominal voltage (III/2): 630 V, contact surface: Tin, contact type: Male, number of potentials: 4, number of rows: 1, number of poles: 4, number of connections: 4, family of articles: PC 6/.. -GL3, pitch: 7.62 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 2.6 mm, number of solder pins per potential: 3, plug-in system: COMBICON PC 6, Plug-in face orientation: Standard, locking: Snap-in lock, fixing type: Snap-in flange, packing type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PC 6/ 4-GL3-7,62 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.