INDUSTRIAL COMPONENT DATA

ZEC 1,0/10-LPV-3,5 C1 1915738 PHOENIX CONTACT PCB connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: ZEC 1,0/10-LPV-3,5 C1



Manufacturer	PHOENIX CONTACT
MPN / Reference	ZEC 1,0/10-LPV-3,5 C1
Catalog number	1915738
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-4B34AC05D5
Generated	2026-11-18

Product Overview

PCB connector
Connector for printed circuit board, nominal section: 1 mm², color: green, nominal current: 8 A, nominal voltage (III/2): 200 V, contact surface: Tin, contact type: Female, number of potentials: 10, number of rows: 1, number of poles: 10, number of connections: 10, family of articles: ZEC 1.0/.. -LPV, pitch: 3.5 mm, mounting: Direct plug-in connection technology, driver/printed circuit board connection direction: 0 °, number of solder pins per potential: 2, plug-in system: ZEC, lock: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data
Orderkey 1915738
Packing unit 50 pc
Minimum order quantity 50 pc
Note Made to Order (non-returnable)
Catalog page Page 365 (C-1-2013)
GTIN 4017918181444
Weight per Piece (excluding packing) 6.540 g
Custom tariff number 85366930
Country of origin GR (Greece)

Dimensions
Length 22.9 mm
Height 7 mm
Width 36.4 mm
Pitch 3.5 mm
Dimension a 35 mm
General
Range of articles ZEC 1,0/..-LPV
Insulating material group I
Rated surge voltage (III/3) 2.5 kV
Rated surge voltage (III/2) 2.5 kV
Rated surge voltage (II/2) 2.5 kV
Rated voltage (III/2) 200 V
Rated voltage (II/2) 320 V
Connection in acc. with standard EN-VDE
Nominal current IN 8 A
Nominal voltage UN 160 V
Nominal cross section 1 mm²
Maximum load current 8 A
Insulating material PA
Flammability rating according to UL 94 V0
Number of positions 10
Standards and Regulations
Connection in acc. with standard EN-VDE
CUL
Flammability rating according to UL 94 V0
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Classifications
eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss 7.027440402eCl@ss 8.027440402eCl@ss 9.027440402
ETIM 3.0EC001121ETIM 4.0EC002643ETIM 5.0EC002637ETIM 6.0EC002637
UNSPSC 6.0130211810UNSPSC 7.090139121409UNSPSC 1139121409UNSPSC 12.0139121409UNSPSC 13.239121409

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ZEC 1,0/10-LPV-3,5 C1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES
Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.