

**INDUSTRIAL COMPONENT DATA**

# SPT-SMD 1,5/ 6-V-5,08 R44 1824459 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: SPT-SMD 1,5/ 6-V-5,08 R44



|                 |                                |
|-----------------|--------------------------------|
| Manufacturer    | PHOENIX CONTACT                |
| MPN / Reference | SPT-SMD 1,5/ 6-V-5,08 R44      |
| Catalog number  | 1824459                        |
| Category        | Printed circuit board terminal |
| Minimum order   | 200 Pcs                        |
| Document ID     | EO-6A9EBE0C12                  |
| Generated       | 2026-09-29                     |

## Product Overview

PCB terminal block

Terminal block for printed circuit board, nominal current: 13.5 A, nominal voltage (III/2): 320 V, nominal section: 1.5 mm<sup>2</sup>, number of potentials: 6, number of rows: 1, number of poles per row: 6, article family: SPT 1.5/.. -V-SMD, pitch: 5.08 mm, connection type: Push-in spring connection, mounting: SMD soldering, driver/printed circuit board connection direction: 90°, color: black, Pin arrangement: Linear pin arrangement, number of solder pins per potential: 2, packaging type: 44 mm wide strap

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

## Additional Product Information

Key Commercial Data

Orderkey 1824459

Packing unit 200 pc

Minimum order quantity 200 pc

Note Made to Order (non-returnable)

Catalog page Page 9 (NTK-2014)

GTIN 4046356816557

Weight per Piece (excluding packing) 5.670 g

Custom tariff number 85369010

Country of origin DE (Germany)

**Dimensions**

Length [ l ] 7.7 mm

Pitch 5.08 mm

Dimension a 25.4 mm

Width [ w ] 29.4 mm

Height 13.6 mm

Height [ h ] 13.6 mm

Pin spacing 7 mm

Hole diameter 1.1 mm

**General**

Range of articles SPT 1,5/-V-SMD

Insulating material group IIIa

Rated surge voltage (III/3) 4 kV

Rated surge voltage (III/2) 4 kV

Rated surge voltage (II/2) 4 kV

Rated voltage (III/3) 250 V

Rated voltage (III/2) 320 V

Rated voltage (II/2) 500 V

Connection in acc. with standard EN-VDE

Nominal current I<sub>N</sub> 13.5 ANominal cross section 1.5 mm<sup>2</sup>

Insulating material LCP

Solder pin surface

Flammability rating according to UL 94 V0

Stripping length 8 mm

Number of positions 6

**Connection data**Conductor cross section solid min. 0.2 mm<sup>2</sup>Conductor cross section solid max. 1.5 mm<sup>2</sup>Conductor cross section flexible min. 0.2 mm<sup>2</sup>Conductor cross section flexible max. 1.5 mm<sup>2</sup>Conductor cross section flexible, with ferrule without plastic sleeve min. 0.2 mm<sup>2</sup>Conductor cross section flexible, with ferrule without plastic sleeve max. 1.5 mm<sup>2</sup>Conductor cross section flexible, with ferrule with plastic sleeve min. 0.2 mm<sup>2</sup>Conductor cross section flexible, with ferrule with plastic sleeve max. 0.75 mm<sup>2</sup>

Conductor cross section AWG min. 24

Conductor cross section....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SPT-SMD 1,5/ 6-V-5,08 R44 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.